

JW MARRIOTT

GREG KOCHALSKI
STRUCTURAL OPTION

THESIS PRESENTATION
SPRING 2007



ALTICOR



JW MARRIOTT.
HOTELS & RESORTS

OUTLINE



JW MARRIOTT

GREG KOCHALSKI

INTRODUCTION

EXISTING STRUCTURE

FLOOR SYSTEM

LATERAL SYSTEM

STRUCTURAL REDESIGN

FLOOR SYSTEM

LATERAL SYSTEM

ARCHITECTURAL REDESIGN

COST ANALYSIS

CONCLUSIONS/RECOMMENDATIONS

INTRODUCTION

JW MARRIOTT

GREG KOCHALSKI



PROJECT INFORMATION

- 24 STORY MARRIOTT SIGNATURE SERIES HOTEL
- LOCATED ALONG THE GRAND RIVER IN DOWNTOWN GRAND RAPIDS, MI
- 340 ROOMS
- 376,000 SQ. FT.
- AMENITIES INCLUDE RESTAURANT, LOUNGE, BUSINESS CENTER, FITNESS CENTER, AND SPA
- STYLISTIC ARCHITECTURE WITH REFLECTIVE GLASS CLADDING
- OPEN AIR ATRIUM
- HEATED HELIPAD



INTRODUCTION

JW MARRIOTT

GREG KOCHALSKI

SITE PLAN



DOWNTOWN

GRAND RAPIDS



INTRODUCTION

JW MARRIOTT

GREG KOCHALSKI



PROJECT TEAM

OWNER- ALTICOR INC.

ARCHITECT- GOETTSCH PARTNERS AND

BETA DESIGN GROUP

STRUCTURAL- THORNTON TOMASETTI ENGINEERS

CONTRACTOR- PEPPER CONSTRUCTION AND

ROCKFORD CONSTRUCTION

MEP- COSENTINI ASSOCIATES



ALTICOR

goettschpartners

 **PEPPER**
CONSTRUCTION

Thornton Tomasetti

 **BETADESIGN**

 **ROCKFORD**
CONSTRUCTION



OUTLINE



JW MARRIOTT

GREG KOCHALSKI

INTRODUCTION

EXISTING STRUCTURE

FLOOR SYSTEM

LATERAL SYSTEM

STRUCTURAL REDESIGN

FLOOR SYSTEM

LATERAL SYSTEM

ARCHITECTURAL REDESIGN

COST ANALYSIS



CONCLUSIONS/RECOMMENDATIONS

STRUCTURE

GREG KOCHALSKI

FOUNDATION

- 200 TON MICRO PILES
- PILE CAPS LOCATED ALONG THE PERIMETER AND BENEATH THE CORE
- 4-7 MICRO PILES PER GROUP



EXISTING STRUCTURE

JW MARRIOTT




GREG KOCHALSKI

FLOOR SYSTEM

- FLAT PLATE R.C.
- SHORT SPANS- 17 FT.
- ONE WAY ACTION
- TYPICAL BAY APPROX 17x35 FT
- 7.5 IN. SLAB
- F'c = 5700 PSI
- BLADE-COLUMNS LOCATED ALONG PERIMETER
- TRANSFER GIRDERS AT LEVELS 3-5

ECCENTRIC LOADING REQUIRES HEAVY TORSIONAL REINFORCING IN BEAM



EXISTING STRUCTURE

JW MARRIOTT





GREG KOCHALSKI

BLADE-COLUMNS

- REDUCE SPANS
- LIMIT SLAB THICKNESS
- MAXIMIZE PATRON VIEWS
- FIT WITHIN INTERIOR PARTITIONS
- BOUNDARY CONFINEMENT AT EDGES

TYPICAL FLOOR WITH RADIAL COLUMNS

CONFINEMENT



EXISTING STRUCTURE




JW MARRIOTT

GREG KOCHALSKI


LATERAL SYSTEM

- TWO PAIRS OF SHEAR WALLS
- F'c VARIES FROM 10 KSI TO 6ksi
- BOUNDARY ELEMENTS FOR INCREASED INERTIA IN EAST-WEST
- 12 IN. THICK IN BOTH DIRECTIONS



HEAVY CONFINEMENT

IN BOUNDARY ELEMENTS



OUTLINE



JW MARRIOTT

GREG KOCHALSKI

INTRODUCTION

EXISTING STRUCTURE

FLOOR SYSTEM

LATERAL SYSTEM

STRUCTURAL REDESIGN

FLOOR SYSTEM

LATERAL SYSTEM

ARCHITECTURAL REDESIGN

COST ANALYSIS

CONCLUSIONS/RECOMMENDATIONS

STRUCTURAL REDESIGN

JW MARRIOTT

GREG KOCHALSKI



PROPOSAL SUMMARY

- RELOCATION TO MONTEREY, CA
- NEW LATERAL SYSTEM
- NEW POST TENSION FLOOR SYSTEM
- USE UPDATED BUILDING CODE

DESIGN GOALS

- ACHIEVE DESIRED NON-LINEAR RESPONSE
- AVOID PITFALLS OF PEER REVIEW
- LIMIT VERTICAL WALLS TO <3.0% OF FLOOR AREA

BUILDING CODES

GRAND RAPIDS

- MBC 3003 (IBC 2003)
- ACI 318 2002
- ASCE 7 2002

MONTEREY


- IBC 2006
- ACI 318 2002
- ASCE 7 2005



POST TENSION SYSTEM

JW MARRIOTT

GREG KOCHALSKI



LABELING SCHEME

CHARACTERISTICS


- TYPICAL SPAN = 35 FT.
- 9.5 IN. PT FLAT PLATE (L/45)
- CLASS U SYSTEM
- BALANCE 85% DEAD LOAD
- 1/2 IN. 270 KSI STRANDS
- $F'c = 4000 \text{ PSI}$

PT Floor Loads		
	Design Loads (psf)	ASCE 7 (psf)
Dead	20	20
Live	40	40

POST TENSION SYSTEM

JW MARRIOTT


GREG KOCHALSKI




POST TENSION SYSTEM

JW MARRIOTT

GREG KOCHALSKI



LARGE BANDED TENDONS





SMALL BANDED TENDONS

POST TENSION SYSTEM

JW MARRIOTT

GREG KOCHALSKI



AVERAGE STRESSES

$$f = -\frac{F}{A} \pm \frac{M_n}{S}$$

$$\frac{F}{A} = 225 \text{ psi}, \quad \frac{M_n}{S} = (\pm 442 \text{ psi}, \pm 79 \text{ psi})$$

$$f = +217 < 6\sqrt{f'_c}$$


$$= -667 < 0.3f'_c$$

$$= +79 < 2\sqrt{f'_c}$$

$$= -529$$

Slab Deflections		
Span	Deflection (in)	Deflection Equivalent
AB	0.268	L/1150
CD	0.361	L/1150

9.5 IN. PT FLAT SLAB WORKS




NONLINEAR RESPONSE

- FORCE DISSIPATION
MECHANISM ENSURES INTEGRITY
- PLASTIC HINGING IN BEAMS,
WALLS APPROACH YIELDING
- DETAILED FOR PROPER
DUCTILITY
- EVEN DEFORMATIONS OVER
HEIGHT

PEER REVIEW

- 256 FT EXCEEDS 240 FT
HEIGHT LIMIT
- REQUIRES “CODE
EQUIVALENT PERFORMANCE”...
- INHERENT UNCERTAINTIES
WHEN INTERPRETING CODE



ANALYSIS METHODS

- EQUIVALENT LATERAL FORCE METHOD
 - MANUAL CALCULATIONS
 - ETABS
- MODAL RESPONSE (DYNAMIC) ANALYSIS
 - ETABS

SPECTRAL RESPONSE PARAMETERS

- $S_{D_S} = 0.97$
- $S_{D_1} = 0.53$
- S.D.C. = D
- S.C. = C
- O.C. = II
- R = 5.0
- $C_D = 4.5$



ETABS CASES & COMBINATIONS

SCALE FACTORS

• STATIC ANALYSIS (ACCIDENTAL TORSION)

- EXZ1 - ECC IN X, CW MOMENT
- EXZ2 - ECC. IN -X, CCW MOMENT
- EYZ1
- EYZ2

$$Ecc.\ Ratio = 0.05 \times A_x$$

• DYNAMIC ANALYSIS (MEMBER FORCES)

- XSPECF
- YSPECF

$$\text{Scale Factor} = (\text{S.F.}_{\text{DYN}}) \times \left(\frac{V_{b\text{ ELF}}}{V_{b\text{ DYN}}} \right) \times 0.85$$


• DYNAMIC ANALYSIS (DISPLACEMENTS)

- XSPECD
- YSPECD

$$\text{Scale Factor} = \frac{386 \times C_d}{R}$$



PIER AND SPANDREL LABELING





COUPLING BEAMS

INFLUENCE...

- PERIOD
- SHEAR (IN WALLS)
- DISPLACEMENTS


CRACKED SECTION

$$I_{\text{effective}} \geq \frac{0.2}{(1 + 3(h/l_n)^2)} \times I_{\text{gross}}$$

ULTIMATE SHEAR

$$V_u \leq \phi \times 8.0 \sqrt{f'_c} \times bd$$

INTERPRETING THE OUTPUT



Varying I_{eff}			
I_e	V_{\max}	V_{norm}	Period
0.10	189	0.814655	2.76
0.16	232	1	2.425
0.5	317	1.366379	1.99
0.75	340	1.465517	1.90



ULTIMATE SHEAR

DETERMINED GROUP, AND WILL BE THE MAXIMUM OF

- $0.8V_{\text{MAX}}$
- V_{AVERAGE}

DETAILING

REINFORCING MUST ENSURE


- PROPER DUCTILITY
- FAILURE IN MOMENT, NOT SHEAR

Level	Shear (K)	Coupling Beam Ultimate Shear			
		Shears		Design Group Shears	
		0.8 V _{max} (K)	V _{average} (K)	0.8 V _{max} (K)	V _{average} (K)
Roof	90				
24	111				
23	113				
22	121				
21	131				
20	142				
19	152				
18	162				
17	171				
16	179				
15	187				
14	194				
13	201				
12	208				
11	214				
10	220				
9	225				
8	229				
7	232				
6	231				
5	228				
4	220				
3	205				
2 Mezz	181				
2	163				

LATERAL SYSTEM

JW MARRIOTT

GREG KOCHALSKI



Beam B1

LATERAL SYSTEM

JW MARRIOTT

GREG KOCHALSKI

DISPLACEMENT

<2.0% HEIGHT (CODE)




<1.0% HEIGHT (IMPOSED)

$$0.01H = 30 \text{ IN.}$$

MAX DISPLACEMENT


16.6 IN. (X)

21.4 IN. (Y)





Displacement




MAX DISPLACEMENT

16.6 IN. (x)

21.4 IN. (Y)

INTERPRETING OUTPUT

- BEAM ACTION IN Y
- FRAME ACTION IN X





SHEAR WALLS

DESIGN CRITERIA

DIRECT SHEAR

- DISTRIBUTES BY AREA
- LIMIT SHEAR TO:

FLEXURE

- DISTRIBUTES BY INERTIA
- REINFORCE TO RESIST TENSION

$$V_u \leq \phi \times 4.0 \sqrt{f'_c} \times t \times l$$



DIRECT SHEAR

$$V_u \leq \phi \times 4.0 \sqrt{f'_c} \times t \times l$$

Pier 3 : $1100 \text{ k} = \phi \times 3.59 \sqrt{f'_c} \times A_v$, where $A_{v3} = 37.33 \text{ ft}^2$

Pier 4 & 5 : $343 \text{ k} = \phi \times 2.24 \sqrt{f'_c} \times A_v$, where $A_{v4/5} = 18.67 \text{ ft}^2$


Pier 6 : $876 \text{ k} = \phi \times 4.11 \sqrt{f'_c} \times A_v$, where $A_{v6} = 26.0 \text{ ft}^2$

Pier 7 & 8 : $350 \text{ k} = \phi \times 3.78 \sqrt{f'_c} \times A_v$, where $A_{v7/8} = *19.5 \text{ ft}^2$

$*A_{v7/8} = 9.77 \text{ ft}^2 \times \cos(33^\circ) + 12.2 \text{ ft}^2 \times \cos(22^\circ)$



INTERPRETING THE OUTPUT



THEORETICAL

A_v (FT^2)	26	37.3	37.3	26
K_v	0.7	1.0	1.0	0.7
DF_v	0.21	0.29	0.29	0.21

ETABS OUTPUT (YSPECF)

V_{OP}	876	1100	1100	876
DF_{OP}	0.22	0.28	0.28	0.22




FLEXURE

REINFORCE TENSION AREAS

- PCA COLUMN
- LOAD CASES DERIVED FROM

ASCE7



MOMENT SIGN CONVENTION

$$\text{ASCE7} : 0.9D + 0.5L \pm 1.0E + 1.0E_v$$

where $E_v = 0.2S_{DS}D$, $S_{DS} = 0.97$, and $L = 0$

ASCE7 then becomes :

- (1) $0.7D + 1.0E_x + 0.3E_y$
- (2) $0.7D + 1.0E_x - 0.3E_y$
- (3) $0.7D - 1.0E_x + 0.3E_y$
- (4) $0.7D - 1.0E_x - 0.3E_y$
- (5) $0.7D + 0.3E_x + 1.0E_y$
- (6) $0.7D - 0.3E_x + 1.0E_y$
- (7) $0.7D + 0.3E_x - 1.0E_y$
- (8) $0.7D - 0.3E_x - 1.0E_y$

Where $E_x = M_x$ due to Earthquake in Y

$E_y = M_y$ due to Earthquake in X

$$D = P_{SELF\ WT} + P_{GRAVITY}$$



REINFORCING

TRENDS:


- HEAVY REINFORCING IN OUTER AREAS OF FLANGES
- LIGHT REINFORCING IN WEBS

Pier Vertical Reinforcing Schedule						
Pier	Rebar #	Rows	Spacing (in)	As (sq. in.)	ρ , per Pier (%)	ρ , per section (%)
3	9	1	16	18	0.26	0.94
4	9	2	6	38	1.41	
5	9	2	6	38	1.41	
6	9	1	11	15	0.40	1.16
7 outer	9	3	3.5	30	1.13	
7 inner	9	2	6.5	24	1.70	
8 outer	9	3	3.5	30	1.13	
8 inner	9	2	6.5	24	1.70	

Pier Horizontal Reinforcing Schedule					
Pier	Rebar #	Rows	Spacing (in)	As (in ² /ft)	ρ , per Pier (%)
3	4	2	10	0.48	0.25
4	5	2	10	0.74	0.26
5	5	2	10	0.74	0.26
6	4	2	10	0.48	0.25
7	5	2	10	0.74	0.26
8	5	2	10	0.74	0.26



VERIFYING THE RESULTS



OUTLINE



JW MARRIOTT

GREG KOCHALSKI

INTRODUCTION

EXISTING STRUCTURE

FLOOR SYSTEM

LATERAL SYSTEM

STRUCTURAL REDESIGN

FLOOR SYSTEM

LATERAL SYSTEM

ARCHITECTURAL REDESIGN

COST ANALYSIS

CONCLUSIONS/RECOMMENDATIONS

ARCHITECTURAL REDESIGN

JW MARRIOTT

GREG KOCHALSKI

AFFECTED AREAS

- STAIRWELLS
- PATRON ELEVATORS
- FIRST FLOOR SERVICE CORRIDOR
AND RESTROOMS
- SECOND FLOOR FIRE CORRIDOR

NOTABLE IBC CODES


1019.1: “*exit enclosure shall not be used for other than egress...*”

1019.1.2: “*no penetrations shall be allowed except those related to exit egress or systems directly related to the function of the exit way...*”




THE ATRIUM IS A LARGE FOCAL POINT OF
THE ARCHITECTURE

TYPICAL FLOOR



GROUND FLOOR



OUTLINE



JW MARRIOTT

GREG KOCHALSKI

INTRODUCTION

EXISTING STRUCTURE

FLOOR SYSTEM

LATERAL SYSTEM

STRUCTURAL REDESIGN

FLOOR SYSTEM

LATERAL SYSTEM

ARCHITECTURAL REDESIGN

COST ANALYSIS

CONCLUSIONS/RECOMMENDATIONS



PRIMARY LOSSES

- PT SYSTEM MORE SKILL INTENSIVE
- LOWER DAILY PRODUCTION
- THICKER SLAB

SECONDARY LOSSES

- DURATION INCREASE
- INTEREST EARNINGS



POST TENSION SYSTEM REQUIRE
LONGER DURATIONS AND MORE
EXPENSIVE LABOR



DIRECT LOSS COMPARISON

Flat Plate	
Location	Grand Rapids
Crew	C-17B
Daily Output (cy)	30.24
Labor Hours (cy)	6.878
Material (\$)	242
Labor (\$)	253
Equipment (\$)	24
Total (\$)	519
Concrete (cy)	5707
Material (\$)	1,381,094
Labor (\$)	1,443,871
Equipment (\$)	136,968
Total (\$)	2,961,933
Incl. O&P (\$)	3,909,752
Duration (weeks)	38

Post Tension (x2.0)	
Location	Monterey
Crew	(2) C-17B
Daily Output (cy)	20
Labor Hours (cy)	8.2
Material (\$)	475
Labor (\$)	630
Equipment (\$)	31
Total (\$)	1136
Concrete (cy)	7228
Material (\$)	3,433,300
Labor (\$)	4,553,640
Equipment (\$)	224,068
Total (\$)	8,211,008
Incl. O&P (\$)	10,427,980
Duration (weeks)	72

Post Tension (x3.0)	
Location	Monterey
Crew	(3) C-17B
Daily Output (cy)	30
Labor Hours (cy)	8.2
Material (\$)	475
Labor (\$)	945
Equipment (\$)	31
Total (\$)	1451
Concrete (cy)	7228
Material (\$)	3,433,300
Labor (\$)	6,830,460
Equipment (\$)	224,068
Total (\$)	10,487,828
Incl. O&P (\$)	13,319,542
Duration (weeks)	48

*ACTUAL DURATION OF 47

WEEKS DUE TO WEATHER

SECONDARY LOSSES

- \$230/NIGHT AVERAGE ROOM PRICE
- 60% OCCUPANCY EXPECTED
- \$8 MILLION LOST IN 25 WEEK DELAY

OUTLINE



JW MARRIOTT

GREG KOCHALSKI

INTRODUCTION

EXISTING STRUCTURE

FLOOR SYSTEM

LATERAL SYSTEM

STRUCTURAL REDESIGN

FLOOR SYSTEM

LATERAL SYSTEM

ARCHITECTURAL REDESIGN

COST ANALYSIS

CONCLUSIONS/RECOMMENDATIONS



NON-LINEAR RESPONSE

- PLASTIC HINGING MECHANISM IN BEAMS
- SHEAR WALLS WELL BELOW YIELD, SYSTEM DEFORMS EVENLY

FLOOR SYSTEM

- POST TENSION SYSTEM Viable ALTERNATIVE
- COSTS OF PT ARE STAGGERING, USE ORIGINAL FLAT PLATE SYSTEM

ARCHITECTURE

- ATRIUM REMAINS FOCAL POINT
- ORIGINAL SPACES ACCOUNTED FOR



JW MARRIOTT

GREG KOCHALSKI

ACKNOWLEDGEMENTS

BERT CRANDELL

BEN KOCHALSKI

PETE JACKSON

JEFF STYLES

ERIKA JOHNSON

DR. BOOTHBY

DR. LEPAGE

ALL AE FACULTY

MOM AND DAD

MY FRIENDS

AND EVERYONE ELSE THAT MADE

THESIS A REALITY

QUESTIONS?