




APPENDIX D





HYATT REGENCY
PITTSBURGH INTERNATIONAL AIRPORT
PITTSBURGH, PA



PC. 2 of 6

INTERIOR

LIVE LOAD REDUCTION ($\leq 100 \text{ psf} \neq \text{NONROOF}$)

$$A_I = 4A_T = 2295 \text{ ft}^2$$

$$\text{BELOW 2} \quad L = L_o \left(0.25 + \frac{15}{\sqrt{A_I}} \right) = 0.563 L_o \geq 0.5 L_o$$

$$\text{BELOW 8} \quad L = L_o \left(0.25 + \frac{15}{\sqrt{72245}} \right) = 0.268 L_o \geq 0.4 L_o$$

BELOW 12

USE 0.4 L_o

COLUMN	BELOW	A _I	LL R (%)	A _T	LL	DL	ROOF LL	ROOF DL
2		2295	0.563	573.75	32.3	57.4	14.3	57.4
8		16065	0.4	4016.25	160.7	401.6	14.3	57.4
12		25245	0.4	6311.25	252.5	631.1	14.3	57.4

$$\text{ROOF LL} = 25 \text{ psf} (573.75 \text{ ft}^2) = 14.3 \text{ k}$$

$$\text{ROOF DL} = 100 \text{ psf} (573.75) = 57.4 \text{ k}$$

$$\text{BELOW 2 LL} = 0.563 (100) (573.75) = 32.3 \text{ k}$$

$$\text{BELOW 2 DL} = 100 (573.75) = 57.4 \text{ k}$$

$$\text{BELOW 8 LL} = 0.4 (100) (4016.25) = 160.7 \text{ k}$$

$$\text{BELOW 8 DL} = 100 (4016.25) = 401.6 \text{ k}$$

$$\text{BELOW 12 LL} = 0.4 (100) (6311.25) = 252.5 \text{ k}$$

$$\text{BELOW 12 DL} = 100 (6311.25) = 631.1 \text{ k}$$

BEAM LL RED

$$A_T = (24)(27) = 648 \text{ ft}^2$$

$$(8.5)(27) = 499.5 = 500 \text{ ft}^2$$

$$A_I = 2A_T = 1296 \text{ ft}^2$$

$$= 1000 \text{ ft}^2$$

$$L = L_o \left(0.25 + \frac{15}{\sqrt{1296}} \right) = 0.67 L_o$$

(MIDDLE)

$$L = L_o \left(0.25 + \frac{15}{\sqrt{1000}} \right) = 0.72 L_o$$

(ENDS)

22-141 50 SHEETS
22-142 100 SHEETS
22-144 200 SHEETS





HYATT REGENCY
PITTSBURGH INTERNATIONAL AIRPORT
PITTSBURGH, PA



PG. 3 OF 6

BEAMS

END $W_u = 1.2(100) + 0.72(1.6)(40) = 166.1 \text{ psf}$

MIDDLE $W_u = 1.2(100) + 0.67(1.6)(100) = 227.2 \text{ psf}$

$W_D = 1.2(100) = 120 \text{ psf}$

END SPAN

$W_u = 166.1(14.5) = 3.1 \text{ klf}$

$W_D = 120(14.5) = 2.2 \text{ k}$

MIDDLE SPAN

$W_u = 227.2(24) = 5.5 \text{ klf}$

$W_D = 120(24) = 2.9 \text{ k}$



$FEM_{BA} = \frac{3.1(18.5)^2}{12} = 88.4 \text{ k}$

$FEM_{BC} = \frac{2.9(24)^2}{12} = 139.2 \text{ k}$

$P_u = 1.2(57.4 + 57.4) + 1.6(32.3) + 0.5(14.3) = 196.6 \text{ k}$


JOINT B

$88.4 \downarrow + 139.2$

$\Delta FEM = 139.2 - 88.4 = 50.8 \text{ k}$

for DESIGN $P_u = 196.6 \text{ k}$

$M_u = \frac{\Delta FEM}{2} = \frac{50.8}{2} = 25.4 \text{ k}$



$FEM_{AB} = \frac{2.2(18.5)^2}{12} = 62.7 \text{ k}$

$FEM_{BC} = \frac{5.5(24)^2}{12} = 264 \text{ k}$

$62.7 \downarrow + 264$

$P_u = 196.6 \text{ k}$

$\Delta FEM = 264 \text{ k} - 62.7 \text{ k} = 201.3 \text{ k}$

for DESIGN $P_u = 196.6 \text{ k}$

$M_u = 100.7 \text{ k}$

22-141 50 SHEETS
22-142 100 SHEETS
22-144 200 SHEETS





HYATT REGENCY
PITTSBURGH INTERNATIONAL AIRPORT
PITTSBURGH, PA



4 of 6

TR4 W14 $P_n = 196.6 \text{ k}$
 $M_n = 100.7 \text{ k}$

$l = 11'$

$P_{eff} = P_n + \alpha M_n = 196.6 + \frac{24}{1.71}(100.7) = 369.2 \text{ k}$

WITH $KL = 11'$ $P_{n, eff} = 369.2 \text{ k}$

USE W14x48, $\phi P_n = 423 \text{ k}$

EXTERIOR

ROOF LL = $25 \left(\frac{18.5}{2} \right) (27) = 61.2 \text{ k}$

ROOF DL = $100 \left(\frac{18.5}{2} \right) (27) = 251.0$

$L = 40 \left(0.25 + \frac{15}{\sqrt{4 \left(\frac{18.5}{2} \right) (27)}} \right) = 0.72 L_0$

LL = $0.72 (40) \left(\frac{18.5}{2} \right) (27) = 7.2 \text{ k}$

DL = $100 \left(\frac{18.5}{2} \right) (27) = 251.0 \text{ k}$

WALL = $(110 \text{ psf}) \left(\frac{4}{12} \right) (11') (27) = 10.9 \text{ k}$

$FEM_{AB} = \frac{3.1(18.5)^2}{12} = 88.4 \text{ k}$

ASSUME $\frac{1}{2}$ INTO COL

$M_u = \frac{88.4}{3} = 29.5 \text{ k}$

$P_u = 1.2(25 + 25 + 10.9) + 1.6(7.2) + 0.5(6.2) = 87.7 \text{ k}$

$P_{u, eff} = 87.7 + 1.71(29.5) = 138.1 \text{ k}$

USE W14x48 FOR SYMMETRY & STACKING PURPOSES

22-141 50 SHEETS
22-142 100 SHEETS
22-144 200 SHEETS





HYATT REGENCY
PITTSBURGH INTERNATIONAL AIRPORT
PITTSBURGH, PA



5 of 6

BELOW 8

INTERIOR

$$P_u = 1.2(401.6 + 57.4) + 1.6(160.7) + 0.5(14.3) = 815.1^k$$

$$M_u \text{ DESIGN} = 100.7^k$$

$$P_{eff} = 815.1 + 1.71(100.7) = 987.3^k$$

USE W14 x 109 $\phi P_n = 1240$

EXTENSION

$$P_u = 1.2(7(25) + 25 + 7(10.4)) + 1.6(7(7.2)) + 0.5(6.2) = 415.3^k$$

$$M_u \text{ DESIGN} = 29.3^k$$

$$P_{eff} = 415.3 + 1.71(29.3) = 465.7^k$$

USE W14 x 53 $\phi P_n = 469^k$
OR W14 x 61 $\phi P_n = 615^k$

BELOW 12

INTERIOR

$$P_u = 1.2(631.1 + 57.4) + 1.6(252.5) + 0.5(14.3) = 1237.4^k$$

$$M_u \text{ DESIGN} = 100.7^k$$

$$P_{eff} = 1237.4 + 1.71(100.7) = 1409.6^k$$

USE W14 x 145 $\phi P_n = 1530^k$

EXTENSION

$$P_u = 1.2(11(25) + 25 + 110_{\text{psf}}(\frac{1}{2})(27)(120)) + 1.6(11(7.2)) + 0.5(6.2) = 644.3^k$$

$$M_u \text{ DESIGN} = 29.3^k$$

$$P_{eff} = 644.3 + 1.71(29.3) = 694.7^k$$

USE W14 x 74 $\phi P_n = 753^k$

22-141 50 SHEETS
22-142 100 SHEETS
22-144 200 SHEETS







HYATT REGENCY
PITTSBURGH INTERNATIONAL AIRPORT
PITTSBURGH, PA



6 OF 6

SUMMARY OF COLUMNS BELOW 2, 8, 12



22-141 50 SHEETS
22-142 100 SHEETS
22-144 200 SHEETS
GAMPAD