

PricewaterhouseCoopers Building

Oslo, Norway



James Wilson

Structural Option

Senior Thesis Presentation 2009

The Pennsylvania State University

- **Introduction**
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion

Bjørsvika B10 A
Oslo, Norway



- **Introduction**
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion



Image Courtesy of Oslo S Utvikling AS



Image Courtesy of Oslo S Utvikling AS

- **Introduction**
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS


Presentation Outline

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion

Spaces



Section 1-1



1st Floor Plan

- Display Room / Shops
- 154 Person Auditorium / Lobby
- Office / Conference Rooms
- Cafeteria / Outdoor Patio
- Vert. Transportation / Tech. Zone



9th Floor Plan



Image Courtesy of Oslo S Utvikling AS

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

Presentation Outline


- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion

Floor System



Precast Hollow Core Concrete Plank

4' wide
11" deep
+ 2" Topping



Structural Option



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

Floor System

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

Presentation Outline

Columns

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

Presentation Outline

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion

Transfer Truss



273 x 16mm = 10.7 x .63 in
323.9 x 6.3 mm = 12.75 x .63.25 in





Image Courtesy of Oslo S Utvikling AS

- Introduction
- **Existing Structural System**
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion

Steel:

Item	Euronorm	ASTM	Fy (ksi)	Fu (ksi)	Ea (ksi)	Va	Density (lb/ft ³)
Columns	S355	A572Gr50	51	74	30 500	.3	50
Beams	S355	A572Gr50	51	74	30 500	.3	50
Reinforcing	B500C	-	-	72	30 500	-	-

Concrete:

Item	Norwegian Standard	Eurocode CEN	f _{ck} (ksi)	f _{cm} (ksi)	E _{cm} (ksi)
Cast in place	B35	C35/45	5	0.46	4 850
Prefabricated	B45	C45/55	6.5	0.55	5 222
Columns	B45	C45/55	6.5	0.55	5 222



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- **Proposal**
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- **Proposal**
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- **Proposal**
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion






Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- **Proposal**
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- **Proposal**
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- Conclusion



Aerial images courtesy of Google Earth



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

Framing Plan

- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion

Live Load: 80 psf
SIMP Dead Load: 15psf
Span: 7.8ft

Results using United Steel Deck Manual:
20 gage 2" LOK- FLOOR composite deck
3.25" thk. Lightweight concrete slab
Provides 2hr fire rating without the need for fireproofing
WWF: 6 x 6 – W2.0 x2.0 reinforcing








Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion

Composite or Non-composite?

Key	Member	Span (ft)	Composite			Non Composite		Most Economical by Equiv. Wt.
			Least Wt. Mem.	# Studs	Equivalent Wt.	Least Wt. Mem.	Wt	
	Typical Int. Beam	19.14	W12x14	8	348	W12x19	364	Composite
	Typical Ext. Girder	23.6	W14x22	12	639	W14x30	708	Composite
	Long span beam	38.5	W14x53	23	2271	W14x68	2618	Composite
	Long Span Ext. Girder	23.9	W14x30	22	937	W14x43	1028	Composite




Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion

Strength – ASCE 7-05 sec2.3 LRFD load combinations:

1. 1.4 Dead
2. 1.2 Dead + 1.6 Live + 0.5 Roof Live
3. 1.2 Dead + 1.6 Roof Live + 0.5 Live

Serviceability - Deflection:

Composite:

Construction Dead Load.....	l/360
Post Composite Live Load.....	l/360
Post Composite Superimposed ..	l/240
Net Total Load.....	l/240

Economy – Camber

Do not camber: Beams less than 25ft
Beams that require less than 3/4" of camber
Beams in braced frames

No shoring

Member Depth limited to 14"



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion

Optimal members were determined by RAM and checked with hand calculations
 Example– Typical Beam and Girder

	Member	L (ft)	Mu	I Req Deflection (in ⁴)			Least Wt. Member	I _{yc} (in ⁴)	I _{zb} (in ⁴)
				Δ _{LL}	Δ _T	Δ _{PC}			
Hand Calc	Beam	19.14	70.5	103	116.4	67.5	W12x14	88.6	101
	Girder	23.62	126.3	203	268.8	108.36	W14x22	199	424
RAM	Beam	19.14	72.4	-	-	-	W12x14	88.6	101
	Girder	23.62	154	-	-	-	W14x22	199	424





Image Courtesy of Oslo S Utvikling AS

Presentation Outline


Final Framing Plan

- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion



3rd Floor Framing Plan

**Members which are part of the lateral system are not labeled



- Introduction
- Existing Structural System
- Proposal
- **Redesign of Gravity System**
- Redesign of Lateral System
- Breadth Study
- Conclusion


Perimeter columns resisting gravity loads only:

Level 1-12: **W10**

Columns resisting gravity + lateral load:

Level 1-12: **W14**

Columns Spliced every 2 stories



Column E-6 Design Summary						
	Floor	Pu (kips)	KL (ft)	Least Wt. Mem.	ΦP_n (kips)	$P_u < \Phi P_n$
Hand Calc.	1	157	12	W10x33	292	OK
	5	293	12	W10x39	351	OK
	9	424	12	W10x49	513	OK
RAM	1	155	12	W10x33	292	OK
	5	287	12	W10x39	351	OK
	9	429	12	W10x49	513	OK



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

Brace Location Study

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion







Image Courtesy of Oslo S Utvikling AS

Architectural Study

Braced Frames at Perimeter



- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

Presentation Outline



- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion

ETABS Model - Preliminary Design


Model of lateral system only was constructed in ETABS to determine optimal framing layout

Wind load application:

- ASCE 7 – 05 – Analytical Procedure
- Wind loads applied at the center of pressure of diaphragm at each level



Levels 5-12



Levels 1-4



Image Courtesy of Oslo S Utvikling AS


- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion

Seismic load application:


ASCE 7 – 05: Equivalent Lateral Force Procedure

Seismic loads applied at the center of mass at each level

✦ = Center of Mass



Levels 5-12



Levels 1-4



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion

Very large axial forces were induced in the columns towards the base of the structure due to the narrow shape of the core



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion




Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion

Members checked under combined loading in an integrated RAM model

1. $1.4(D + F)$
2. $1.2(D + F + T) + 1.6(L + H) + 0.5(Lr \text{ or } S \text{ or } R)$
3. $1.2D + 1.6(Lr \text{ or } S \text{ or } R) + (L \text{ or } 0.8W)$
4. **$1.2D + 1.6W + L + 0.5(Lr \text{ or } S \text{ or } R)$**
5. $1.2D + 1.0E + L + 0.2S$
6. $0.9D + 1.6W + 1.6H$
7. $0.9D + 1.0E + 1.6H$







Image Courtesy of Oslo S Utvikling AS



12th floor




5th floor




1st floor


Elevation 3



12th floor



5th floor



1st floor


Elevation 4



12th floor



5th floor



1st floor

Elevation 5



12th floor



5th floor



1st floor

Elevation 6.8



Elevation 3




Elevation 4



Elevation 5



Elevation 6.8



Elevation 7



Elevation 8




Elevation 9



Elevation A



12th floor



5th floor




1st floor

Elevation 7



12th floor




5th floor



1st floor


Elevation 8



12th floor




5th floor



1st floor


Elevation 9



12th floor




5th floor




1st floor

Elevation A



Elevation C




Elevation D



12th floor



5th floor



1st floor

Elevation C



12th floor



5th floor




1st floor

Elevation D

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion


Building Deflection at 12th story:

Wind – Larger deflection at south end



$$H / 400 = 4.38 \text{ in} > 3.7 \rightarrow \text{OK}$$

Seismic – Larger deflection at North end




Tensional irregularity type 1a
 $\Delta x < C_d \Delta x / l$ (ASCE7-05 sec 12.8-15)



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion



Concrete substructure acts as a base to distribute loads to pile foundations

Outriggers help distribute loads to the perimeter



Image Courtesy of Oslo S Utvikling AS

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- **Breadth Study**
- Conclusion



- Elevator relocated
- Duct shaft relocated
- Wall increase from 11.8" to 15"
- Elongated stairwell



Proposed Design

Existing Design

Presentation Outline

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- **Breadth Study**
- Conclusion

Cost comparison

Composite Concrete Deck vs. Precast Concrete Plank

Composite Concrete Deck on Composite Steel Frame					
Quantity	Description	Extended Cost (\$)			
		Material	Labor	Equipment	Total
150000 S.F.	Metal Decking	279,000	69,000	6,000	354,000
660 Ton	Structural Steel	1,518,000	250,800	87,120	1,855,920
1500 C.S.F	WWF 6 x 6	23,475	33,000	-	56,475
1960 C.Y.	L.W. Concrete	286,160	-	-	286,160
14871 Ea.	Studs - 3/4"	8,030	11,153	5,651	24,835
150000 S.F.	Concrete Finish	-	73,500	3,000	76,500
Total =		\$ 2,653,889.57			

Precast Concrete Plank on Steel Frame					
Quantity	Description	Extended Cost (\$)			
		Material	Labor	Equipment	Total
430 Ton	Structural Steel	989,000	163,400	56,760	1,209,160
150000 S.F.	Precast Plank, 10" thick	1,147,500	126,000	78,000	1,351,500
923 C.Y.	2" Concrete Topping	97,838	-	-	97,838
150000 S.F.	Concrete Finish	-	52,500	6,000	58,500
2758 Ea.	Shear Stud - 3/4"	1,489	2,069	1,048	4,606
Total =		\$ 2,721,603.86			



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- **Breadth Study**
- Conclusion

Schedule comparison

Construction schedule for composite concrete deck and precast concrete plank created in Microsoft Project

Results for Construction of structure :

- + Composite steel deck = 52 days
- + Precast Concrete Plank = 40 days

23% schedule reduction with use of precast plank



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- **Conclusion**

Conclusions – Gravity System

- Composite concrete deck on composite steel beams and girders is the most viable floor system for the PwC building if located in Boston
- However, precast concrete plank has potential to be more economical due to cost saving incurred by reduction of construction schedule



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

Conclusions – Lateral System

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- **Conclusion**



Image Courtesy of Oslo S Utvikling AS

Presentation Outline

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- Redesign of Lateral System
- Breadth Study
- **Conclusion**

Acknowledgements

I would like to thank the following for their generous support and assistance on this senior thesis:

- + Prof. M. Kevin Parfitt - Thesis Consultant
- +Pareto Investments - for granting me permission to use the PwC-building as the subject of this year long project.
- +All the Professors at The Pennsylvania State University - for their assistance over the past five years.
- + Friends and family - for their patients and support



Image Courtesy of Oslo S Utvikling AS

Questions?



Image Courtesy of Oslo S Utvikling AS

12.3-1 Horizontal Structural Irregularities		
	Irregularity	Must Comply with Reference Section:
1a	Torsional Irregularity $\Delta 1$ (in.) = 1.53 $\Delta 2$ (in.) = 2.67 $\rightarrow 1.2((\Delta 1 + \Delta 2)/2) = 2.52 < \Delta 2$	12.7.3 16.2.2
3	Diaphragm Discontinuity Irregularity \rightarrow Slit diaphragm at the bottom four stories	12.7.3 16.2.2
5	Nonparallel Systems-Irregularity \rightarrow Vertical lateral force resisting elements are not parallel or symmetric about major orthogonal axes.	12.7.3 16.2.2

- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion

Members
Braces = HSS10x10x.5
Beams = W18x86
Columns = W14x132

→ 1/3 of deflection




Image Courtesy of Oslo S Utvikling AS

Presentation Outline


- Introduction
- Existing Structural System
- Proposal
- Redesign of Gravity System
- **Redesign of Lateral System**
- Breadth Study
- Conclusion

Next Step

Moment Frames at the perimeter

- Braced frames
- Moment frames

Reduce large axial forces at the core



Special Steel Plate Shear Walls



Image Courtesy of Oslo S Utvikling AS