

Appendices

The pages following this page contain the following Appendices:

A: Wind Load Calculations	63
B: Seismic Load Calculations.....	66
C: Gravity System Design	69
D: Lateral System Design	88
E: Green Roof Study	106
F: Acoustic Study.....	113
G: Building Plans	117
H: Bibliography	126



Appendix A: Wind Load Calculations

Wind Criteria & Calculated Variables

Wind Criteria	
Basic Wind Speed (V)	90 mph
Wind Exposure Category	B
Occupancy Factor	II
Importance Factor	1
Wind Directionality Factor (K_d)	0.85
Topographic factor (K_{zL})	1
Number of Stories	9
Building Height (Ft.)	94
N-S Building Length (Ft.)	169.75
E-W Building Length (Ft.)	133.5
NE-SW Building Length (Ft.)	200.75
NW-SE Building Length (Ft.)	210.75
L/B in N-S Direction	1.27
L/B in E-W Direction	0.79
L/B in NE-SW Direction	1.05

figure 6-1C

table 6-1

table 6-4

sect 6.5.7.1-2

Gust Factor			
Variable	Wind Direction		
	N-S	E-W	NE-SW
Stiffness	Rigid	Rigid	Rigid
B (Feet)	133.50	169.75	210.75
L (Feet)	169.75	133.50	200.75
h (Feet)	94.00	94.00	94.00
c	0.30	0.30	0.30
Z	56.40	56.40	56.40
I _z	0.27	0.27	0.27
L _z	202.95	159.61	240.02
ϵ	0.33	0.33	0.33
Q	0.77	0.73	0.76
gQ & gv	3.40	3.40	3.40
G	0.80	0.77	0.79

	Wind Direction		
	N-S Direction	E-W Direction	NE-SW Direction
C _p , Windward	0.8	0.8	0.8
C _p , Leeward	-0.3	-0.5	-0.2
Gust Factor	0.795	0.773	0.788
GCpi	0.18	0.18	0.18

figure 6-6

figure 6-5

Wind Pressures

Height (Feet)	K _z	q _z	Wind Pressures (psf)		
			N-S Windward	N-S Leeward	N-S Total
94	0.97	17.10	13.95	-7.16	21.11
90	0.96	16.92	13.81	-7.16	20.97
80	0.93	16.39	13.38	-7.16	20.53
70	0.89	15.69	12.80	-7.16	19.96
60	0.85	14.98	12.23	-7.16	19.38
50	0.81	14.28	11.65	-7.16	18.81
40	0.76	13.40	10.93	-7.16	18.09
30	0.7	12.34	10.07	-7.16	17.23
25	0.66	11.63	9.49	-7.16	16.65
20	0.62	10.93	8.92	-7.16	16.07
0-15	0.57	10.05	8.20	-7.16	15.36

Height (Feet)	K_z	q_z	Wind Pressures (psf)		
			E-W Windward	E-W Leeward	E-W Total
94	0.97	17.10	13.64	-9.68	23.32
90	0.96	16.92	13.50	-9.68	23.18
80	0.93	16.39	13.08	-9.68	22.76
70	0.89	15.69	12.52	-9.68	22.20
60	0.85	14.98	11.96	-9.68	21.64
50	0.81	14.28	11.39	-9.68	21.07
40	0.76	13.40	10.69	-9.68	20.37
30	0.7	12.34	9.85	-9.68	19.53
25	0.66	11.63	9.28	-9.68	18.96
20	0.62	10.93	8.72	-9.68	18.40
0-15	0.57	10.05	8.02	-9.68	17.70

Wind Story Force, Shear and Overturning Moment Spreadsheets

Wind (North-South)						
Level	Height (Feet)	Tributary Area (Feet)	Total (psf)	Story Force (Kips)	Story Shear (Kips)	Overturning Moment (k-ft)
roof	90	9	21.00	25.28	25.28	2275.40
8	80	10	20.54	27.71	53.00	4492.57
7	70	10	19.97	27.04	80.04	6385.40
6	60	10	19.39	26.27	106.31	7961.77
5	50	10	18.82	25.51	131.82	9237.03
4	40	10	18.10	24.64	156.46	10222.79
3	30	10	17.23	23.58	180.04	10930.27
2	20	10	16.37	21.85	201.90	11367.35
1	10	10	15.36	20.51	222.40	11572.41
ground	0	0	0.00	0.00	222.40	11572.41
						Total

Wind (East-West)						
Level	Height (Feet)	Tributary Area (Feet)	Total (psf)	Story Force (Kips)	Story Shear (Kips)	Overturning Moment (k-ft)
roof	90	9	23.28	35.54	35.54	3198.50
8	80	10	22.78	39.03	74.56	6320.54
7	70	10	22.21	38.19	112.75	8993.51
6	60	10	21.65	37.23	149.98	11227.08
5	50	10	21.09	36.28	186.25	13040.86
4	40	10	20.38	35.20	221.45	14448.76
3	30	10	19.54	33.88	255.33	15465.23
2	20	10	18.7	31.73	287.07	16099.92
1	10	10	17.71	30.06	317.13	16400.55
ground	0	0	0	0.00	317.13	16400.55
						Total



Appendix B: Seismic Load Calculations

Loads for SCBF

System-Specific Seismic Design Values and Coefficients

Seismic Criteria	
Occupancy Category	II
Importance Factor	1.000
Seismic Category	D
Site Class	C
Spectral Acceleration for Short Periods (Ss)	1.572
Spectral Acceleration for 1 Second Periods (S1)	0.617
Site Coefficient, Fa	1.000
Site Coefficient, Fv	1.300
Seismic Design Category	D
R Factor	6.000
S_{MS}	1.572
S_{M1}	0.802
S_{DS}	1.048
S_{D1}	0.535
Deflection Amplification Cd	5.00
Overstrength Factor	2.00

N-S Coefficient Variables	
Cu	1.400
T, min	0.720
Ta	0.604
T _L	8
	0.175
Cs, min	0.124
	1.376
Cs, larger than	0.051

table 12.8-1
Building period
Equation 12.8-7
ASCE 7-05 pg 228
Equation 12.8-2
Equation 12.8-3
Equation 12.8-4
Equation 12.8-6

E-W Coefficient Variables	
Cu	1.400
T, min	0.845
Ta	0.604
T _L	8
	0.175
Cs, min	0.105
	0.998
Cs, larger than	0.051

table 12.8-1
Section 12.8.2
Equation 12.8-7
ASCE 7-05 pg 228
Equation 12.8-2
Equation 12.8-3
Equation 12.8-4
Equation 12.8-6



Approximate Building Weight Calculations

These were used at the beginning of the design phase when all weights were not known once the structure was designed the actual weight was found and a verification was made to ensure the correct weight was in fact used.

Roof Weight					
Dead Load (psf)	Snow Load	Partition Load	Perimeter Wall Load	Perimeter Length	Roof Area
121	20<30 so NA.	-	47	760	14750
Total Roof Weight =	2145.08	kips			

Typical Floor Weight Upper Floors					
Dead Load	Snow Load	Partition Load	Perimeter Wall Load	Perimeter Length	Floor Area
71	-	20	47	760	14750
Total Floor Weight =	1699.45	kips			

Typical Floor Weight Lower Floor					
Dead Load	Snow Load	Partition Load	Perimeter Wall Load	Perimeter Length	Floor Area
71	-	20	47	760	14750
Total Floor Weight =	1699.45	kips			

Appendix C: Gravity System Design

Sample Gravity Member Design

These were early designs to give a relative depth and see how the system will be. The final design has less beam as part of the optimization process but these calculations were not repeated for the relative nature between the two is reasonable.

equally spaced beams at 7'-0"

Deck Design

LL = 40 psf or 100 psf, 15 psf
DL = 15 psf superimposed

Total Load:
 $40 + 15 = 55 \text{ psf}$
 or $100 + 15 = 115 \text{ psf}$

need 3 1/4" min. for furring
 use lightweight.

use the larger load so the same deck can be used throughout

3-Span Condition

2VL+22 has unstored length 7'-4" & can carry 236 psf at 7'0" spacing

Beam B-1 Design

$f_y = 50 \text{ ksi}$
 $f'_c = 3 \text{ ksi}$

$\text{ULL} = 15 \text{ psf}$
 $\text{WDL} = 15 + 92 \text{ psf}$

$W_u = 1.2(15)4.8 + 1.6(55) = 156.4$

$M_o = 0.174 (7') (23.3)^2 = 74.1 \text{ k-ft}$

Try $a = 1.0 \text{ in}$


$y_c = 5.5 - 1.0/2 = 5 \text{ in}$

5'2" using this for ease of table usage.

$b_{eff} = \left\{ \begin{array}{l} \frac{l}{2} = 3.5' = 42'' \text{ controls} \\ \frac{23.3}{4} = 5.83' = 70'' \end{array} \right.$

	<p>From Table 3-19 pg. 1 W10x19 most econ.</p> <p>$y_2 = 5$ $\phi M_{pc} = 140$ $\sum q_n = 96.1$</p> <p>check $a = \frac{96.1}{0.85(3)(42)} = 0.9 < 1.0$ so good.</p> <p>Studs: 3/4" Stud L.W.C., 3 ksf $Q_n = 17.2$ Deck \perp web direction 1 stud $studs = \frac{9(96.1)}{17.2} = 11.2 \rightarrow 12$ studs.</p> <p>LL Deflection $c_{ULL} = 55$ psf $\Delta = \frac{5(50)(7)(23.3)^4(1728)}{384(29000)(243)} = 0.36''$</p> <p>Limit to $\lambda/360$ $\frac{23.3(12)}{360} = 0.77''$</p>	
--	--	--





Studs:

$$Q_n = 21^k$$
$$\text{studs} = \frac{2(180)}{21} = 17.2 \rightarrow 18 \text{ studs.}$$


LL Deflection


WLL = 55 psf (ignoring the 100 due to very small area)

$$\Delta = \frac{5(55)(17.6')(28')^4(1728)}{384(21000)(897)} = 0.51''$$
$$\delta = \frac{28(12)}{360} = 1.13''$$

4/6










Restrained Assembly Rating	Type of Protection	Concrete Thickness & Type (1)	U.L. Design No. (2,3,4)	Classified Deck Type		Unrestrained Beam Rating
				Fluted Deck	Cellular Deck (5)	
2 Hr. (continued)	Sprayed Fiber	2" NW&LW	859 *	2VLI,3VLI	2VLP,3VLP	1.1.5.2.3 Hr.
			822 *	2VLI,3VLI	2VLP,3VLP	1 Hr.
			825 *	1.5VLI,2VLI,3VLI	2VLP,3VLP	1.1.5.2 Hr.
			831 *	2VLI,3VLI	2VLP,3VLP	1.1.5.2 Hr.
			832 *	1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5.2.3 Hr.
			833 *	1.5VLI,2VLI,3VLI	2VLP,3VLP	1.5 Hr.
			847 *	2VLI,3VLI	3VLP	1.1.5.3 Hr.
			858 *	2VLI,3VLI	2VLP,3VLP	1.1.5.2.4 Hr.
			861 *	12VLI,3VLI		1.1.5 Hr.
			870 *	1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.2 Hr.
			871 *	2VLI,3VLI	2VLP,3VLP	1.1.5.2.3 Hr.
	Unprotected Deck	2 1/2" LW	862 *	2VLI,3VLI		1 Hr.
			864 *		3VLP	1.5 Hr.
			860 *	2VLI,3VLI		1.1.5.2 Hr.
		3 1/4" LW	733 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			826 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5.2 Hr.
			840 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			902 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			907 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.2 Hr.
			913 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1 Hr.
			916 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5.2.3 Hr.
			918 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			919 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			920 #	2VLI,3VLI	2VLP,3VLP	1.5 Hr.
	4 1/2" NW	4 1/2" NW	902 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			916 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5.2.3 Hr.
			918 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.
			919 #	1.5VL,1.5VLI,2VLI,3VLI	1.5VLP,2VLP,3VLP	1.1.5 Hr.

Ram Optimization Design


It should be noted that these design are the final but certain small changes were made to the typical bay in the report per this authors judgments based on minimum sizes, this mainly is around the W8x10's in the corridors.

Typical Floor


Floor Type: Typical



Floor Type: Typical




Floor Type: Typical




Roof Level


Floor Type: Roof



Floor Type: Roof



Floor Type: Typical



Beam to Girder Connection

Beam	W12x50
tw	0.37 in
Fy	50 ksi
Fu	65 ksi
T	9.25 in
Ag	14.6 in ²
Ho	10.5 in

Single Row of Bolts

V_u 18.2 kips
of bolts 1.14 use 2

1 Eccentric Shear of the Bolt group

Shear
 ϕR_n 15.9 kips

Bearing
 ϕR_n 29.3625 kips

Tearout
 ϕR_n 21.41016 kips

e 4.38

Table 7-7

S 3 in spacing
n 2 # of bolts

4	1.67
4.38	1.57625
5	1.42

ϕV_n 25.06238 kips > 18.2

2 Max Plate Thickness

t 0.4375 > t_p and tw
L_{eh} 1.5 ok

3	Plate shear Yielding		
	L	6 in	
	ϕV_n	48.6	> 18.2
4	plate shear rupture		
	ϕV_n	41.59688	> 18.2
5	Block Shear		
	Table 9-3a	46.2	
	Table 9-3b	72.9	
	Table 9-3c	76.7	
	ϕR_n	44.6625 kips	> 18.2
6	Beam Web tp>tw		
	shear yield		
	ϕR_n	438	
	shear rupture		
	ϕR_n	408.1106	
7	Plate Flexure yield		
a	2.875		
M _u	52.325		
f _v	8.987654321		
F _c r	35.6235461		
ϕM_n	108.2065213 > M _u	ok	

Plate	Fy	36 ksi	Bolts	dia	0.75 in
	Fu	58 ksi		Grade	A325-N
	t	0.375 in		Shear Str.	15.9 ksi

8 Flexural Rupture of the plate

Zplate 2.390625
 ϕM_n 103.9922 > M_u

8 Flexural Rupture of the plate

λ 0.663643 < 0.7

8 weld size

tweld 3.75 sixteenths use $4/16"$

Girder to Column Connection

Girder	W14x53	
tw	0.37	
Fy	50	
Fu	65	
tf	0.66	
Ag	15.6	
d	13.9	

Single Row of Bolts

V_u 24.5 kips
 # of bolts 1.54 use 6

1 Eccentric Shear of the Bolt group

Shear
 ϕR_n 15.9 kips

Bearing
 ϕR_n 29.3625 kips

Tearout
 ϕR_n 21.41016 kips

e 7.38

Table 7-7

S 3 in spacing
 n 2 # of bolts

7	1.99
7.38	1.91125
8	1.78


ϕV_n 30.38888 kips > 24.5

2 Max Plate Thickness

t 0.4375 > tp and tw
 Leh 1.5 ok



3	Plate shear Yielding		
L	9 in		
ϕV_n	72.9	>	24.5 ok
4	plate shear rupture		
ϕV_n	70.95938	>	24.5 ok
5	Block Shear		
Table 9-3a	51.8		
Table 9-3b	117		
Table 9-3c	132		
ϕR_n	63.3 kips	>	24.5
6	Beam Web tp>tw		
shear yield			
ϕR_n	468		
shear rupture			
ϕR_n	437.3606		
7	Plate Flexure yield		
a	5.875		
M _u	143.9375		
f _v	8.065844		
F _c r	35.66234		
ϕM_n	243.7298	> M _u	ok



8 Flexural Rupture of the plate

Z_{plate} = 6.609375
 $\phi M_n = 287.5078 > M_u$

9 Plate Buckling

$\lambda = 1.209347 > 0.7$
 $\phi F_{cr} = 24.37314$

$\phi M_n = 161.0912 > M_u$

10 weld size

t_{weld} = 3.75 sixteenths use 4/16"





Appendix D: Lateral System Design

Center of Mass and Rigidity

Center of Rigidity for SCBF		
Story	X Direction	Y Direction
Roof	73.14	84.53
8	73.12	84.53
7	73.25	84.53
6	73.54	84.53
5	73.97	84.52
4	74.54	84.52
3	74.66	84.52
2	75.01	84.51
1	72.53	84.49

Center of Mass for SCBF		
Story	X Direction	Y Direction
Roof	54.00	81.76
8	53.95	81.94
7	53.95	81.94
6	53.91	81.95
5	53.86	81.95
4	53.88	81.95
3	53.89	81.95
2	53.88	81.94
1	58.11	72.98

Amplification Factor

Amplification Factor, Ao in the N-S Direction for SCBF							
Story	δA (in)	δB (in)	δavg (in)	δmax (in)	Ax	% torsion Δ	Torsion Irreg.
Roof	3.8	2.99	3.395	3.8	0.87	1.12	Good
8	3.21	2.53	2.87	3.21	0.87	1.13	Good
7	2.63	2.08	2.355	2.63	0.87	1.12	Good
6	2.11	1.67	1.89	2.11	0.87	1.13	Good
5	1.59	1.27	1.43	1.59	0.86	1.12	Good
4	1.18	0.95	1.06475	1.18	0.85	1.11	Good
3	0.74	0.6	0.67	0.74	0.85	1.12	Good
2	0.41	0.34	0.375	0.41	0.83	1.10	Good
1	0.11	0.095	0.1025	0.11	0.80	1.07	Good

Amplification Factor, Ao in the E-W Direction for SCBF							
Story	δA (in)	δB (in)	δavg (in)	δmax (in)	Ax	% torsion Δ	Torsion Irreg.
Roof	3.63	3.865	3.7475	3.865	0.74	1.02	Good
8	3.06	3.27	3.165	3.27	0.74	1.04	Good
7	2.52	2.685	2.6025	2.685	0.74	1.03	Good
6	2.01	2.14	2.075	2.14	0.74	1.03	Good
5	1.51	1.61	1.56	1.61	0.74	1.04	Good
4	1.12	1.185	1.1525	1.185	0.73	1.02	Good
3	0.69	0.74	0.715	0.74	0.74	1.03	Good
2	0.39	0.42	0.405	0.42	0.75	1.07	Good
1	0.26	0.25	0.255	0.26	0.72	1.02	Good

Inherent Torsion

Inherent Torsion in the N-S Direction with SCBF					
Story	COM	COR	Eccentricity	Story Force (k)	Torsion (ft-k)
Roof	81.76	84.53	2.77	398.08	1103
8	81.94	84.53	2.59	280.44	726
7	81.94	84.53	2.59	245.39	636
6	81.95	84.53	2.58	210.33	543
5	81.95	84.52	2.57	175.28	450
4	81.95	84.52	2.57	140.22	360
3	81.95	84.52	2.57	105.17	270
2	81.94	84.51	2.57	70.11	180
1	72.98	84.49	11.51	35.06	404
				Total	4672

Inherent Torsion in the E-W Direction with SCBF					
Story	COM	COR	Eccentricity	Story Force (k)	Torsion (ft-k)
Roof	54.00	73.14	19.14	398.08	7619
8	53.95	73.12	19.17	280.44	5376
7	53.95	73.25	19.3	245.39	4736
6	53.91	73.54	19.63	210.33	4129
5	53.86	73.97	20.11	175.28	3525
4	53.88	74.54	20.66	140.22	2897
3	53.89	74.66	20.77	105.17	2184
2	53.88	75.01	21.13	70.11	1481
1	58.11	72.53	14.42	35.06	506
				Total	32453

Accidental Torsion

Accidental Torsion in the N-S Direction for SCBF					
Story	Width Bx (Ft)	5% Bx (Ft)	Story Force (K)	Ax Factor	Torsion (Ft-K)
Roof	130	6.5	467.4	1.00	3038.2
8	130	6.5	329.3	1.00	2140.4
7	130	6.5	288.1	1.00	1872.8
6	130	6.5	247.0	1.00	1605.2
5	130	6.5	205.8	1.00	1337.7
4	130	6.5	164.6	1.00	1070.2
3	130	6.5	123.5	1.00	802.6
2	130	6.5	82.3	1.00	535.1
1	130	6.5	41.2	1.00	267.5

Accidental Torsion in the E-W Direction for SCBF					
Story	Width By (Ft)	5% By (Ft)	Story Force (K)	Ax Factor	Torsion (Ft-K)
Roof	167	8.35	398.1	1.00	3323.97
8	167	8.35	280.4	1.00	2341.67
7	167	8.35	245.4	1.00	2049.01
6	167	8.35	210.3	1.00	1756.26
5	167	8.35	175.3	1.00	1463.59
4	167	8.35	140.2	1.00	1170.84
3	167	8.35	105.2	1.00	878.17
2	167	8.35	70.1	1.00	585.42
1	167	8.35	35.1	1.00	292.75

Lateral Design Spot Check

Lateral SCBF Spot Check, Brace.	
<u>SCBF Brace Design</u>	
$P_D = 16.4 \text{ k}$	$F_y = 46$
$P_L = 10$	
$P_{QE} = 285 \text{ k}$	
$\Omega = 2.0$	
$\beta = 1.3$	
$S_{OS} = 1.048$	
$\frac{10.67}{14.62} (285) = 207.99 \text{ Tension}$	
<u>max compressive force</u>	
$P_u = (1.2 + 0.2S_{OS})P_0 + \beta P_{QE} + 0.5P_L$	
$P_u = (1.2 + 0.2(1.048))(16.4) + 1.3(285) + 0.5(10)$	
$= 398.6$	
<u>max tension force</u>	
$T_u = (0.9 - 0.2S_{OS})P_0 + \beta P_{QE}$	
$= (0.9 - 0.2(1.048))(16.4) + 1.3(-285)$	
$= -359.2$	
<u>Unbraced Length</u>	
$L = \sqrt{10^2 + 10.67^2}$	
$= 14.62'$	



Try HSS 10 x 10 x 5/8"

$$A_g = 21 \text{ in}^2$$

$$b = 10 \text{ in}$$

$$t_{nom} = 0.581 \text{ in}$$

$$r = 3.8$$

Using table I-6 the section meets local buckling requirements.

Check Slenderness

$$\frac{kL}{r} \leq 4.0 \sqrt{\frac{E}{f_y}}$$

use $k = 1.0$ per Table C-C2.2.

$$\frac{kL}{r} = \frac{1.0(14.62)(12)}{3.8} = 46.2$$

$$4.0 \sqrt{\frac{E}{f_y}} = 4 \sqrt{\frac{29000}{46}} = 100 \quad \text{since } 46.2 < 100 \text{ then good.}$$

Determine Compression Strength

Section E3 specs.

$$4.71 \sqrt{\frac{E}{f_y}}$$

$$4.71 \sqrt{\frac{29000}{46}} = 118.3 > 46.2 \text{ then use.}$$

$$F_{cr} = \left[0.658 \frac{F_y/F_c}{\pi^2} \right] F_y$$

$$F_c = \frac{\pi^2 E}{(\frac{kL}{r})^2}$$

$$= \frac{\pi^2 (29000)}{46.2^2}$$

$$= 134,1 \text{ ksi}$$



$$F_{cr} = \left[0,658 \frac{46}{134,1} \right] 46$$

$$= 39,8 \text{ kN}$$

$$\phi P_n = 0,9 F_{cr} A_g$$

$$= 0,9 (39,8)(21)$$

$$= 753,1 \text{ kips}$$

$$P_u = 398,6 < 753,1^k \text{ so - ok.}$$

Determine Tension Strength

yielding on the section.

$$P_u = F_y A_g$$

$$\phi P_n = 0,9 (46)(21)$$

$$= 869,4^k$$

$$P_u = 357,2 < 869,4^k \text{ so! ok}$$

Seismic Connections Calculations

Column Splice

Column	W14x176	Plate	
Fy	50	W	6
d	13.1	t	1
tf	1.11	L	12
tw	0.71	weld	
Z	85.4	Fy	0.375
			36

1 Splice demands

V_u 231.744 kips
M_u 2135 k-in

2 Plate shear strength

V_n 116.64 per plate total 233.28 note greater than demand found in Ram

3 splice weld strength

C1	1		
L	12		
kL	5 k	0.416667	0
ex,al	0		
a	0		
	C		
0.4	5.29		
0.42	5.38		
0.5	5.85		

4 Required weld D

1.793678 sixteenths use 3/16"

Brace to Beam to Column

Brace	HSS9x9x5/8		Beam	W18x65	
A _g	18.7 in ²		d	18.4	
r	3.4		k _{des}	1.17	
t _{nom}	0.625		t _w	0.48	
D	10		t _f	0.77	
t _{des}	0.581		F _y	50	
F _y	46 ksi		F _u	65	
F _u	58 ksi		N		
Length act	11 ft				
gusset plate clip			1 in		

1 Expected tensile Strength of the Brace

$$R_y = 1.6$$

$$T_u = 1376.32 \text{ kips}$$

2 Expected max compression strength of the brace

$$Kl/r = 38.82353 \leq 118.2608$$

so:

$$F_e = 189.7$$

$$F_{cr} = 41.5604$$

nominal Compressive Strength

$$P_n = 1367.836$$

3 Interface Forces

P _u	1372.078 kips	e _b	9.25 in
V _c	682.8203 kips	e _c	6.5 in
H _c	177.5333 kips	β	25 in
H _b	826.2125 kips	α	30.25 in
V _b	252.6435 kips		
R	50.23569		

4 **column to Gusset weld Design**

f_v 27.31281
 f_a 7.101331
 f_{avg} 28.22
 f_r 35.27611

D_{min} 12.67102 use **13 sixteenths**

5 **yielding of the gusset plate**

ϕr_n 45 > f_v and f_a so ok

6 **column web yielding**

ϕr_n 32.25 > $r_u = f_a$ so ok

7 **column web crippling**

N 0.77
 r_n 545.8825
 ϕr_n 409.4119 > Huc so ok

8 **beam to Gusset weld Design**

f_v 27.31281
 f_a 8.351851
 f_{avg} 28.56
 f_r 35.70152

D_{min} 12.82382 **13 sixteenths**

9 **beam web yielding**

ϕr_n 24 > r_u so ok

10 **beam web crippling**

N 30.25
 r_n 581.6507
 ϕr_n 436.238 > Vub so ok

Column		Plate	A 36
d	14.7	Fy	50
k des	1.63	Fu	65
tw	0.645	t	1.5
tf	1.03		
Fy	50	Bolts	
Fu	65	dia	0.75 in
N		Grade	A325-N
		Shear Str.	15.9 kips

11 beam connection

Flange Connection

use CJP welds

Shear tab

Vu 50
of bolts 3.14 use 4

Plate length 11.5
Plate Thickness 0.239464 use 0.25

Gross Shear
 ϕV_n 62.1 > Vu so ok

Block Shear
 ϕV_n 53.05 > Vu so ok

Bolt Shear, bearing, and tearout

table 10-9a allows 52.2 kips > Vu so ok

Weld Size
Dmin 2.5 use 3 sixteenths



Brace to Beam Mid-Span

Brace	HSS9x9x5/8		Beam	W18x60	
A_g	18.7 in ²		d	18.4 in	
r	3.68		k _{des}	1.15	
t _{nom}	0.625 in		tw	0.45 in	
D	9 in		tf	0.75 in	
t _{des}	0.581 in		F _y	50 ksi	
F _y	46 ksi		F _u	65 ksi	
F _u	58 ksi		N	35.2	
Length act	11 ft				

1 Expected tensile Strength of the Brace

R_y 1.6

T_u 1376.32 kips

2 Brace to Gusset weld Design

max fillet weld size

D \leq 10.91 try 10 /sixteenths

minimum length of 4 welds

l_w \geq 24.7 Use(L) 25 in

min gusset plate thickness

t_{min} 0.007521 use 1.5 in

3 Shear lag check of the brace

A_{e req} 26.36628 18.7 so not good

A_n 16.66875 in²
A_{ecp} 9.697534 in²

so reinforcing plates 2, 5/8" by 8" plate

w D_{min} 0.5625 use 9 sixteenths



4 **Determine brace forces**

$$KL/r \quad 35.86957 \leq \quad 118.2608$$

so:

$$F_e \quad 222.2312$$

$$F_{cr} \quad 42.18248$$

nominal Compressive Strength

$$P_n \quad 1388.31$$

5 **Determine forces at gusset beam interface**

Shear Force

$$V \quad 1954.888 \text{ kips}$$

Tension Force

$$T \quad 8.478069 \text{ kips}$$

Moment

$$M \quad 17984.97 \text{ k-in}$$

6 **Design weld at the gusset beam interface**

$$\text{Gusset plate length} \quad 69.75 \text{ in}$$

$$S_w \quad 810.8438 \text{ in}^3/\text{in}$$

$$f_v \quad 28.02707 \text{ kip/in}$$

$$f_a \quad -0.12155 \text{ kip/in}$$

$$f_b \quad 22.18057 \text{ kip/in}$$

$$f_{peak} \quad 35.66675 \text{ kips/in}$$

$$f_{avg} \quad 35.74218 \text{ kips/in}$$

$$f_p/f_a \quad 0.99789 < \quad 1.25$$

so:

$$f_r \quad 44.67773 \text{ kips/in}$$

min weld size

$$D \geq \quad 16.04803 \quad \text{use} \quad \text{CJP}$$

Plate	A 36
Fy	50 ksi
Fu	65 ksi

7 **Compression buckling of gusset plate check**

plate t 1.5 (from part 2)
buckling length 19 in

r 0.433013 in

Kl/r 52.65434
 ϕF_{cr} 26.3 table 4-22

whitmore width
lw 25 in

Lw 37.84982 in

ϕR_n 1493.175 kips > 1388.31 so ok

8 **tension yielding of gusset**

ϕR_n 2554.863 kips > 1376.32 so ok

9 beam web local buckling

max comp load per length of gusset
fc 22.05902 kip/in

max tens load per length of gusset
ft 22.30212 kip/in

length of gusset subject to tensile forces

lt 35.06611 in

ϕF_{ywtw} 30.25 > 22.05902 so ok

10 Beam web Crippling

Ru 382.5462 kips

Rn 923.5717

ϕR_n 692.6788 kips > 382.5462 so ok

11 free edge buckling of gusset plate

max free edge length

Lfg max 27.09359 in

outer edge to brace

Lfg 24.82226 in < 27.09359 so ok

inner brace to brace(one stiffner)

Lfg 34.1629 in > 27.09359 so ng

inner brace to brace(two stiffner)

Lfg 13.45811 < 27.09359 so ok

Inverted V

Brace	HSS9x9x5/8	Beam	W36x282
A _g	18.7 in ²	d	37.1 in
r	3.4	b _f	16.6 in
t _{nom}	0.625 in ²	t _w	0.885 in
D	10 in ²	t _f	1.57 in
t _{des}	0.581 in ²	F _y	50 ksi
F _y	46 ksi	F _u	65 ksi
F _u	58 ksi	A _g	82.9 in ²
Length act	11 ft	weight	0.282 klf
		I _x	17900 in ⁴
		Z _x	1200 in ³
		r _x	15.3
		R _y	3.76
		S _x	92 in ³

1 assumed force in the tension brace

$$R_y = 1.6$$

$$P_t = 1376.32$$

2 assumed force in the compression brace

$$KL/r = 38.8 < 118.2608$$

so:

$$\begin{aligned} F_e &= 189.7 \\ F_{cr} &= 41.5604 \end{aligned}$$

$$\begin{aligned} P_n &= 777.1796 \\ \phi P_n &= 699.4616 \\ P_c &= 233.1539 \end{aligned}$$

3 determine the unbalanced vertical load on the beam

$$\begin{aligned} P_{ty} &= 1251.2 \text{ kips} \\ P_{cy} &= 211.9581 \text{ kips} \end{aligned}$$

$$Q_b = 1039.242 \text{ kips}$$

4 Determine axial force in the beam

$$\begin{aligned} P_{ty} &= 1376.32 \text{ kips} \\ P_{cy} &= 233.1539 \text{ kips} \end{aligned}$$



P_u 804.7369 kips

5 Determine moment in the beam

M_{qe} 5715.831

M_u 5715.831

6 check element slenderness

λ_f 5.286624

λ_p 9.151612

λ_w 38.2

λ_p 90.55279

6 check unbraced length

L_p 12.2 manual table 3-2

L_b 10.36667

7 Determine Flexural Strength

M_n 5000

φM_n 4500

Story height 10 ft
frame width 22 ft
.5 frame w 11 ft

Column dc 15.2 in

8 Determine Compression Strength

K_x/r_x 17.2549
K_y/r_y 35.10638

From Manual

φF_{cr} 39.2 ksi
φcP_n 3249.68 kips

9 Consider second-order effects

B1	1.01	P _{el}	73434.89
B2	1.0		

P _r	804.7369
M _{rx}	5779.162

10 Check Combined Loading

P _r /P _c	0.207406 < .2	P _c	3880
so		M _c	4240
1.066713 < 1.0			

11 Determine Shear in the beam

V _{qe}	1039.242
V _u	1039.242

12 Check Shear Strength

table 3-2		
φV _n = φRv1	1110 >	1039.242 so ok



Appendix E: Green Roof Study

Existing LEED Score Card

UMCP Bldg 7 -- LEED 2.2 Checklist & Responsibility Matrix									
CREDIT	CRITERIA	INTENT AND REQUIREMENT	Attempt?			# of Points	Responsible for Analysis and/or Documentation	Documentation Pending	Status
			Y	N	?				
Sustainable Sites									
Pre-requisite	Construction Activity Pollution Prevention	Prevent loss of soil during construction by storm water runoff and/or wind erosion, including protecting topsoil by stockpiling for reuse. Prevent sedimentation of storm sewer or receiving streams and/or pollution with dust and particulate matter. Erosion control plan conforms to 2003 EPA Construction General Permit, or local Erosion and Sedimentation Control standards, whichever is more stringent.				—	AMT		100% CD
Credit SS 1.0	Site Selection	Avoid the development of inappropriate sites (e.g.- prime agricultural land, flood plains, previous parkland, wetlands) and reduce the environmental impact from the location of a building on a site.	1		1	1	DCI	Provide a written narrative and plan of the existing site to verify that it is a predeveloped area.	Done
Credit SS 2.0	Development Density & Community Connectivity	Construct on a previously developed site AND within a 1/2 mile of a dense residential zone (average of 10 units per acre) AND within 1/2 mile of 10 basic services AND with pedestrian access between the building and the services.	1		1	1	DCI	Overlay a 1/2 mile radius on a Google map and highlight the locations of services and outline / calculate the residential density.	Done
Credit SS 3.0	Brownfield Redevelopment	Rehabilitate damaged sites where development is complicated by real or perceived environmental contamination, reducing pressure on undeveloped land.		1					
Credit SS 4.1	Alternative Transport. - Public	Locate building within 1/4 mile of a commuter rail, lite rail, or subway station OR 1/4 mile of 2 or more bus lines.	1		1	1	DCI / AMT	Document the 2 nearest stops on any 2 separate routes of the UM Shuttle, within	Done
Credit SS 4.2	Alternative Transport. - Bike Storage	Provide suitable means for securing bicycles, in a covered location, for 15% or more of building occupants.		1		1	DCI/UMCP/CMC	Documented the locations in the Mowatt Garage. Need to provide cut-sheets of the proposed racks to verify the capacity of 55 bikes.	100% CD
Credit SS 4.3	Alternative Transport. - Low-Emitting Vehicles	Provide preferred parking for low-emitting or fuel-efficient vehicles for 5% of the total parking capacity of the site	1		1	1	UMCP/DCI/AMT	The submitted CIR was answered favorably. We need to upload actual Green Sticker Program info to site. UMCP to provide.	100% CD
Credit SS 4.4	Alternative Transport. - Parking	Provide no new on-site parking	1		1	1	DCI	Residents will park in existing Mowatt Garage	Done
Credit SS 5.1	Site Development - Protect or Restore Habitat	On greenfield sites, limit site disturbance including earthwork and clearing of vegetation to 40 feet beyond the building perimeter, 5 feet beyond primary roadway curbs, walkways, and main utility branch trenches, and 25 feet beyond previous paving areas that require additional staging areas in order to limit compaction in the paved area. On previously developed sites, restore a minimum of 50% of the remaining open area by planting native or adapted vegetation.		1					
Credit SS 5.2	Site Development - Maximize Open Space	Reduce the development footprint to exceed the local zoning's open space requirement for the site by 25%.	1						
Credit SS 6.1	Stormwater Design Quantity Control	No net increase in the rate or quantity of stormwater runoff from existing to developed conditions	1					Calcs did not appear favorable.	
Credit SS 6.2	Stormwater Design Quality Control	Treatment systems designed to remove 80% of the average annual post development total suspended solids by implementing Best Management Practices.		1				Calcs did not appear favorable	
Credit SS 7.1	Heat Island Effect - Non-Roof	Provide shade or a high-SRI on at least 50% of non-roof impervious surfaces on the site, including parking lots, walkways, plazas.							
Credit SS 7.2	Heat Island Effect - Roof	Use ENERGY STAR Roof compliant, high-reflectance AND high emissivity roofing (initial reflectance of at least .65 and three-year-aged reflectance of at least .5 when tested in accordance with ASTM E408) for a minimum of 75% of the roof surface OR install a green vegetated roof for at least 50% of the roof area.	1		1	1	DCI	This credit could be achieved with a white TPO roof membrane	100% CD

UMCP Bldg 7 -- LEED 2.2 Checklist & Responsibility Matrix								
CREDIT	CRITERIA	INTENT AND REQUIREMENT	Attempt?			Responsible for Analysis and/or Documentation	Documentation Pending	50% CD 100% CD Constr Post-Conn
			Y	N	% # of Points			
Credit SS 8.0	Light Pollution Reduction	Do not exceed Illuminating Engineering Society of North America (IESNA) footcandle level requirements AND design interior and exterior lighting such that zero direct-beam illumination leaves the building site. (e.g. must be full cut-off luminaires and no up-lighting)	1		1	BKM	Verify compliance with required security lighting	100% CD
Water Efficiency								
Credit WE 1.1	Water Efficient Landscaping - Reduce by 50%	Use high-efficiency irrigation technology such as micro-irrigation systems, moisture sensors, and weather database controllers.	1		1	MRA/BKM	Credit information has been uploaded and marked complete.	Done
Credit WE 1.2	Water Efficient Landscaping - No Potable Water Use or No Irrigation	Use only captured rain water for at additional 50% reduction in potable water for irrigation needs OR do not install permanent landscape irrigation systems.						
Credit WE 2.0	Innovative Wastewater Technologies	Reduce the use of municipally provided potable water for building sewage conveyance by a minimum of 50% OR treat 100% of wastewater on site to tertiary standards.	1					
Credit WE 3.1	Water Use Reduction - 20% Reduction	Employ strategies that in aggregate use 20% less water than the water use calculated for the building (not including irrigation) after meeting the Energy Policy Act of 1992 fixture performance requirements. (e.g. waterless urinals, low-flow fixtures).	1		1	DCI/BKM	Utilize water flow-restrictors in all faucets and showers. Utilize "low flush" toilets in apartments.	100% CD
Credit WE 3.2	Water Use Reduction - 30%	Exceed the potable water use reduction by an additional 10% (30% total efficiency increase).	1		1	DCV/BKM	Utilize newer "ultra-low dual flush" toilets in apartments?	100% CD
Energy and Atmosphere								
Pre-requisite	Fundamental Building Systems Commissioning	Verify and ensure that fundamental building elements and systems are designed, installed and calibrated to operate as intended through best practice commissioning procedures.			—	WT/BKM/CDC	Need to engage a commissioning agent	Post-Conn
Pre-requisite	Minimum Energy Performance	Design to meet building energy efficiency and performance as required by ASHRAE/IESNA 90.1-2004 or the local energy code, whichever is more stringent. Analyze expected baseline building performance using the			—	BKM/WT		
Pre-requisite	Fundamental Refrigerant Management	Zero use of CFC-based refrigerants in new building HVAC&R systems.			—	BKM/VVT		
Credit EA 1.1 - 1.5	Optimize Energy Performance	Exceed the requirements of ASHRAE 90.1-2004 by 14%, demonstrated by whole building simulation	2		2	DCI/BKM/WT	15-SEER furnaces, consider water heating options	100% CD
Credit EA 2.0	Renewable Energy	Use of on-site renewable energy systems.	1					
Credit EA 3.0	Additional Commissioning	Implement comprehensive best practice commissioning procedures which at a minimum includes third party quality control assurance.	1		1			
Credit EA 4.0	Enhanced Refrigerant	Install base building level HVAC and refrigeration equipment and fire suppression systems that do not contain HFCFs or Halon.	1		1	BKM	Energy Modeler suggested this as an easy credit. BKM agrees.	100% CD
Credit EA 5.0	Measurement & Verification	Comply with the installed equipment requirements for continuous metering as stated in Option B: Methods by Technology of the US DOE's International Performance Protocol (IMPVP) for the following: lighting and systems, cooling loads, building specific process energy efficiency	1		1	BKM/WT	Post-commissioning study in lieu of a metering plan compliant with the IMPVP requirements.	100% CD
Credit EA 6.0	Green Power	Encourage the development and use of grid-source, renewable energy technologies on a net zero pollution basis.	1					
Materials and Resources								
Pre-requisite	Storage & Collection of Recyclables	Provide an easily accessible area that serves the entire building that is dedicated to the separation, collection and storage of materials for recycling including (at a min) paper, glass, plastics and metal.			—	DCI/WT/CDC	Individual bins on each floor and collection in the main trash room, as typical SCC buildings operate.	None
Credit MR 1.1	Building Reuse - 75%	Maintain at least 75% of existing building structure and shell. This is calculated in square feet.	1					

UMCP Bldg 7 -- LEED 2.2 Checklist & Responsibility Matrix									
CREDIT	CRITERIA	INTENT AND REQUIREMENT	Attempt?			# of Points	Responsible for Analysis and/or Documentation	Documentation Pending	50% CD 100% CD Contr Post-Contr
			Y	N	?				
Credit MR 1.2	Building Reuse - 100%	Maintain an additional 25% (100% total) of existing building structure and shell (exterior skin and framing excluding window assemblies). This is.	1						
Credit MR 1.3	Building Reuse - 50%	Maintain 50% of existing building interior	1						
Credit MR 2.1	Construction Waste Management - Divert 50% from stream.	Develop a waste management plan. Recycle and/or salvage 50% (by weight) of construction, demolition, and land clearing waste (total waste-stream).	1		1	WT	Will keep track of tickets.		Post-Contr
Credit MR 2.2	Construction Waste Management - Divert 75% from stream.	Recycle and/or salvage an additional 25% (75% total by weight) of the construction, demolition, and land clearing debris (total waste-stream).	1		1	WT	Will keep track of tickets.		Post-Contr
Credit MR 3.1	Materials Reuse - 5%	Specify salvaged or refurbished materials for 5% of building materials. This is calculated by dollar value.	1						
Credit MR 3.2	Materials Reuse - 10%	Specify salvaged or refurbished materials for 10% of building materials. This is calculated by dollar value.	1						
Credit MR 4.1	Recycled Content - 10%	Use materials with recycled content such that the sum of the post-consumer + 1/2 pre-consumer constitutes at least 10% of total value of materials in the project. This is calculated by dollar value.	1		1	DCI/WT	Look at steel, concrete, carpet, tile, exterior cladding, etc.		Post-Contr
Credit MR 4.2	Recycled Content - 20%	Use materials with recycled content such that the sum of the post-consumer + 1/2 pre-consumer constitutes at least 20% of total value of materials in the project. This is calculated by dollar value.	1						
Credit MR 5.1	Regional Materials - 10%	Specify a minimum of 10% building materials that are extracted, harvested, and manufactured within a radius of 500 miles. This is.		1		DCI/WT	Look at concrete, brick, gypsum board, etc.		Post-Contr
Credit MR 5.2	Regional Materials - 20%	Specify a minimum of 20% building materials that are extracted, harvested, and manufactured within a radius of 500 miles. This is calculated by dollar value.		1					
Credit MR 6.0	Rapidly Renewable Materials	Specify rapidly renewable building materials for 5% of total building materials. This is calculated by dollar value.		1					
Credit MR 7.0	Certified Wood	Use a minimum of 50% of wood-based materials certified in accordance with the Forest Steward Council guidelines for wood building components including framing, flooring, finishes, furnishings, and non-rented temporary construction applications such as bracing, concrete formwork and	1		1	DCI/WT	Must also consider casework, base moulding and all interior wood doors.		Post-Contr
Indoor Environmental Quality (IEQ)							12		
Pre-requisite	Minimum IAQ Performance	Meet the minimum requirements of voluntary consensus standard ASHRAE 62.1-2004. Ventilation for Acceptable Indoor Air Quality and approved Addenda. (e.g. Locate building outdoor air intakes away from loading areas, building exhaust fans, cooling towers, and other sources of contamination).				—	BKM		
Pre-requisite	Environmental Tobacco Smoke Control	Prevent exposure of building occupants and systems to Environmental Tobacco Smoke (ETS). Zero exposure of nonsmokers to ETS by prohibition of smoking in the building or within 25' of the building entrance.				—	UMCP/CMC	UMCP buildings are non-smoking and smoking is prohibited within 25' of entrances	Done
Credit EQ 1.0	Outdoor Air Delivery Monitoring	Install a permanent carbon dioxide (CO ₂) monitoring system that provides feedback on space ventilation performance in a form that affords operational adjustments.	1						
Credit EQ 2.0	Increased Ventilation Effectiveness	For mechanically ventilated buildings, design ventilation systems that result in an air change effectiveness greater than 30% above the minimum as determined by ASHRAE 62.1-2004. For naturally ventilated spaces demonstrate compliance with the recommendations of the Carbon Trust Good Practice Guide 237 (1998)	1						

UMCP Bldg 7 -- LEED 2.2 Checklist & Responsibility Matrix									
CREDIT	CRITERIA	INTENT AND REQUIREMENT	Attempt?			# of Points	Responsible for Analysis and/or Documentation	Documentation Pending	50% CD 100% CD Constr Post-Com
			Y	N	?				
Credit EQ 3.1	Construction IAQ Management Plan - During Construction	Develop and implement an Indoor Air Quality Management Plan such that during construction, meet or exceed the minimum requirements of the Sheet Metal and Air Conditioning National EMC Association (SMACNA) IAQ Guideline for Occupied Buildings under Construction 1995 (applied to 5 areas: HVAC protection, source control, pathway interruption, housekeeping, and scheduling), AND protect stored on-site or installed absorptive materials from moisture damage, AND replace all filtration media immediately prior to occupancy w/ MERV 13.	1			1	WT	Requires MERV 8 filtration during construction and MERV 13 filtration to be installed at end of construction. BKM research indicates we can comply.	Post-Com
Credit EQ 3.2	Construction IAQ Management Plan - Before Occupancy	Conduct a building flushout with new filtration media at 14,000cf outside air for each square foot of floor area, after construction ends and prior to occupancy, OR conduct a baseline indoor air quality testing procedure consistent with current EPA protocol.	1			1	WT	Depending on scheduling and time-of-year, this may need to be achieved in various ways	Post-Com
Credit EQ 4.1	Low-Emitting Materials - Adhesives & Sealants	Adhesives and sealants must meet or exceed the VOC limits of South Coast Air Quality Management District Rule # 1168.	1			1	DCI/WT	Specs and submittal verification	100% CD
Credit EQ 4.2	Low-Emitting Materials - Paints & Coatings	Paints and coating must meet or exceed the VOC and chemical component limits of Green Seal requirements.	1			1	DCI/WT	Specs and submittal verification	100% CD
Credit EQ 4.3	Low-Emitting Materials - Carpet Systems	Carpet systems must meet the Carpet and Rug Institute Green Label Indoor Air Quality Test Program.	1			1	DCI/WT	Specs and submittal verification	100% CD
Credit EQ 4.4	Low-Emitting Materials - Composite Wood & Agrifiber Products	Composite wood products must contain no added urea-formaldehyde resins.	1			1	DCI/WT	Specs and submittal verification	100% CD
Credit EQ 5.0	Indoor Chemical Pollutant Source Control	Employ a permanent entryway system (i.e., grills or grates) to keep dirt from entering the building at high volume entryways, AND provide areas with deck to deck partitions with separate exhaust air and negative pressure for chemical use, housekeeping and copying/printing rooms, AND drains plumbed for approp. disposal of liquid chemical concentrate waste.	1			1	DCI/BKM/WT	Provide entrance mats in both building vestibules and separate the janitor closets	100% CD
Credit EQ 6.1	Controllability of Systems - Lighting	Provide individual lighting controls for a minimum of 90% of building occupants AND for all shared multi-occupant spaces	1			1	DCI/BKM		100% CD
Credit EQ 6.2	Controllability of Systems - Thermal Comfort	Provide controls for each individual for airflow, temperature, and lighting for 50% of regularly occupied areas (or provide operable windows) AND provide system controls for all shared multi-occupant spaces	1			1	DCI/BKM		100% CD
Credit EQ 7.1	Thermal Comfort - Design	Provide for a thermally comfortable environment that supports the productive and healthy performance of the building occupants by complying with ASHRAE Standard 55-2004 for thermal comfort standards including humidity control within established ranges per climate zone.	1			1	BKM		100% CD
Credit EQ 7.2	Thermal Comfort - Verification	Implement a survey of residents regarding thermal comfort performance and effectiveness of humidification and/or dehumidification systems in the building.	1			1	BKM/CMC		Post-Com
Credit EQ 8.1	Daylight and Views 75%	Achieve a minimum Daylight Factor of 2% (excluding all direct sunlight penetration) in 75% of all space occupied for critical visual tasks, not including copy rooms, storage areas, mechanical, laundry, and other low occupancy support areas.	1					Calcs did not achieve required Daylight Factor	
Credit EQ 8.2	Daylight and Views 90%	Direct line of sight to vision glazing while seated from 90% of all regularly occupied spaces, not including copy rooms, storage areas, mechanical, other low occupancy support areas.	1			1	DCI	Preliminary calcs completed - will add to templates on USGBC site	100% CD

UMCP Bldg 7 -- LEED 2.2 Checklist & Responsibility Matrix									
CREDIT	CRITERIA	INTENT AND REQUIREMENT	Attempt?			# of Points	Responsible for Analysis and/or Documentation	Documentation Pending	50% CD 100% CD Constr Post-Com
			Y	N	?				
Innovation in Design									
	Innovation in Design	Provide design teams and projects the opportunity to be awarded points for exceptional performance above requirements set by the LEED Rating System and/or innovative performance in categories not specifically				5			
Credit ID 1.1	Possible Innovation Credit 1	Campus-wide Transportation Management Plan	1			1	UMCP/DCI	Describe the university's programs of ride-sharing, encouraged bike use, flex-vehicles to minimize the impacts of vehicles on campus. Alternative	Done
Credit ID 1.2	Possible Innovation Credit 2	Heat Island Effect (Non-Roof) Exemplary Performance (100%)	1			1	DCI/MRA/WT	Use high-albedo paving for all new hardscape surfaces	100% CD
Credit ID 1.3	Possible Innovation Credit 3	Green Cleaning Program	1			1	UMCP/CMC	Use only "green" products for general cleaning and disinfecting of interior spaces	100% CD
Credit ID 1.4	Possible Innovation Credit 4	Education of Campus Community About Building	1			1	UMCP/CMC	Develop a program or curriculum which teaches the community about the "green" aspects of the building	100% CD
Credit ID 2.0	LEED Accredited Professional	Support and encourage the design integration process required by a LEED Green Building project and streamline the application and certification process by having at least one principal participant of the project team who has successfully completed the LEED Accredited	1			1	DCI/BKM/WT		Done
			TOTAL POINTS (including innovation Credits)			37	19	1	37
		LEED Certified = 26-32, Silver = 33-38, Gold = 39-51, Platinum = 52 or more							

Water Collection Design Calculations

Locations	Roof Area (SF)	Rain (inches)	Cubic Ft of Rain	Gallons of Water
College Park, MD	14,750.00	44	54,083.33	404,543.33
San Diego, CA	14,750.00	5	6,145.83	45,970.83

Locations	Water Consumed by green roof (inch per month)	Excess water for Sanitary System (Gallons)	Average Supply per month to tank (Gallons)	Required Tank Size (Cubic Feet)	Provided Tanks Sizes (Gallons)
College Park, MD	2	386,155.00	32,179.58	4,302.08	2 @ 1000
San Diego, CA	0.125	44,821.56	3,735.13	499.35	1 @ 500

Drain Sizing

Sizing and Placement of MIFAB Roof Drains

CHART B:

HORIZONTAL STORM DRAIN CAPACITY IN GPM FOR SLOPES GIVEN WITH MAXIMUM SERVICEABLE ROOF AREA IN SQUARE FEET BASED ON SYSTEM CAPACITY

DRAIN PIPE SIZE (INCHES)	1/8 INCH PER FOOT SLOPE	1/4 INCH PER FOOT SLOPE	1/2 INCH PER FOOT SLOPE
DRAIN CAPACITY (GPM)	MAXIMUM ROOF AREA (SQUARE FEET)	DRAIN CAPACITY (GPM)	MAXIMUM ROOF AREA (SQUARE FEET)
3	34	822	48
4	78	1880	1160
5	139	3340	197
6	223	5350	315
8	479	11500	679
10	863	20700	1217
12	1388	33300	1958
15	2479	59500	3500


Roof Drain Sizing - Example

A warehouse is being built in a geographical area where the maximum hourly rainfall (See Page RD-6) is 2.8 inches per hour. The building will be 200'x400' and have a flat roof with no appreciable vertical surfaces.

Roof Drainage System Layout indicated by the sizing example

CALCULATIONS:

- Total area to be drained (200 x 400) 80,000 Sq. ft.
- Number of drains required 8
(From sizing rule, one drain per 10,000 sq. Ft.)
- Rainfall conversion from in. per hour to GPM (0.0104 x 2.8 x 80,000) 2330
- Expected flow from drain (GPM ÷ number of drains) (2330 ÷ 8) 292
- Size of leader (from Chart A) 6 inch vertical
- Size of horizontal storm sewers (from Chart B 1/4/ foot slope, combined flow of vertical leaders) 8,10,12,15 inches



Roof Drain Sizing: Other Considerations

• OVERFLOW DRAINAGE

Overflow scuppers and drains, as essential components of the roof drainage system, are employed to prevent potentially damaging overloading of roof structures. They must be installed in conformance with local codes. Generally, scuppers are installed in adjacent parapet walls no more than 5 inches above the low point of the roof at a ratio of at least one scupper per 20,000 sq. ft. of roof area. Overflow drains of the same size as the roof drains having above roof inlet elevation as specified by code, connected to drain lines independent from the roof drains, may be installed in lieu of scuppers.

• VERTICAL WALLS

Finally, vertical walls that project above and permit storm water to drain on the roof area to be drained must be considered when planning the roof drainage system. An acceptable rule to follow in sizing roof drains, leaders, and horizontal drainage piping is to add one half of the area of any vertical wall that diverts rainwater to the roof to the projected area of that roof. By multiplying the area thus obtained by the GPM/sq. ft. conversion of inches per hour rainfall, the new total GPM discharge requirement is determined for the roof.



Appendix F: Acoustic Study

Space Noise and Listening Requirements

Type of Space (and Listening Requirements)	Preferred Range of Noise Criteria	Equivalent dBA Level*
Concert halls, opera houses, broadcasting and recording studios, large auditoriums, large churches, recital halls (for excellent listening conditions)	< NC-20	< 30
Small auditoriums, theaters, music practice rooms, large meeting rooms, teleconference rooms, audiovisual facilities, large conference rooms, executive offices, small churches, courtrooms, chapels (for very good listening conditions)	NC-20 to NC-30	30 to 38
Bedrooms, sleeping quarters, hospitals, residences, apartments, hotels, motels (for sleeping, resting, relaxing)	NC-25 to NC-35	34 to 42
Private or semiprivate offices, small conference rooms, classrooms, libraries (for good listening conditions)	NC-30 to NC-35	38 to 42
Large offices, reception areas, retail shops and stores, cafeterias, restaurants, gymnasiums (for moderately good listening conditions)	NC-35 to NC-40	42 to 47
Lobbies, laboratory work spaces, drafting and engineering rooms, general secretarial areas, maintenance shops such as for electrical equipment (for fair listening conditions)	NC-40 to NC-45	47 to 52
Kitchens, laundries, school and industrial shops, computer equipment rooms (for moderately fair listening conditions)	NC-45 to NC-55	52 to 61

* Do not use A-weighted sound levels (dBA) for specification purposes. Spectrum shapes and noise characteristics can vary widely for background noises with identical A-weighted sound levels (see Chap. 1).

Air Space Transmission Loss

Airspace (in)	Improvement in TL (dB)					
	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
2	5	7	19	25	30	30
4	10	12	24	30	35	35

Floor and Roof Assembly constructions for STC and IIC

TL DATA FOR COMMON BUILDING ELEMENTS*

Building Construction	Transmission Loss (dB)						STC Rating	IIC Rating†		
	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz				
Walls^{2-6‡}										
<i>Monolithic:</i>										
1. 3/8-in plywood (1 lb/ft ²)	14	18	22	20	21	26	22			
2. 26-gauge sheet metal (1.5 lb/ft ²)	12	14	15	21	21	25	20			
3. 1/2-in gypsum board (2 lb/ft ²)	15	20	25	31	33	27	28			
4. 2 layers 1/2-in gypsum board, laminated with joint compound (4 lb/ft ²)	19	26	30	32	29	37	31			
5. 1/32-in sheet lead (2 lb/ft ²)	15	21	27	33	39	45	31			
6. Glass-fiber roof fabric (37.5 oz/yd ²)	6	9	11	16	20	25	16			
<i>Interior:</i>										
7. 2 by 4 wood studs 16 in oc with 1/2-in gypsum board both sides (5 lb/ft ²)	17	31	33	40	38	36	33			
8. Construction no. 7 with 2-in glass-fiber insulation in cavity	15	30	34	44	46	41	37			
9. 2 by 4 staggered wood studs 16 in oc each side with 1/2-in gypsum board both sides (8 lb/ft ²)	23	28	39	46	54	44	39			
10. Construction no. 9 with 2 1/4-in glass-fiber insulation in cavity	29	38	45	52	58	50	48			
11. 2 by 4 wood studs 16 in oc with 5/8-in gypsum board both sides, one side screwed to resilient channels. 3-in glass-fiber insulation in cavity (7 lb/ft ²)	32	42	52	58	53	54	52			
12. Double row of 2 by 4 wood studs 16 in oc with 3/8-in gypsum board on both sides of construction. 9-in glass-fiber insulation in cavity (4 lb/ft ²)	31	44	55	62	67	65	54			
13. 6-in dense concrete block, 3 cells, painted (34 lb/ft ²)	37	36	42	49	55	58	45			
14. 8-in lightweight concrete block, 3 cells, painted (38 lb/ft ²)	34	40	44	49	59	64	49			
15. Construction no. 14 with expanded mineral loose fill in cells	34	40	46	52	60	66	51			
16. 6-in lightweight concrete block with 1/2-in gypsum board supported by resilient metal channels on one side, other side painted (26 lb/ft ²)	35	42	50	64	67	65	53			
17. 2 1/2-in steel channel studs 24 in oc with 5/8-in gypsum board both sides (6 lb/ft ²)	22	27	43	47	37	46	39			
18. Construction no. 17 with 2-in glass-fiber insulation in cavity	26	41	52	54	45	51	45			
19. 3 5/8-in steel channel studs 16 in oc with 1/2-in gypsum board both sides (5 lb/ft ²)	26	36	43	51	48	43	43			
20. Construction no. 19 with 3-in mineral-fiber insulation in cavity	28	45	54	55	47	54	48			
21. 2 1/2-in steel channel studs 24 in oc with two layers 5/8-in gypsum board one side, one layer other side (8 lb/ft ²)	28	31	46	51	53	47	44			
22. Construction no. 21 with 2-in glass-fiber insulation in cavity	31	43	55	58	61	51	51			
23. 3 5/8-in steel channel studs 24 in oc with two layers 5/8-in gypsum board both sides (11 lb/ft ²)	34	41	51	54	46	52	48			
24. Construction no. 23 with 3-in mineral-fiber insulation in cavity	38	52	59	60	56	62	57			
<i>Exterior:</i>										
25. 4 1/2-in face brick (50 lb/ft ²)	32	34	40	47	55	61	45			
26. Two wythes of 4 1/2-in face brick, 2-in airspace with metal ties (100 lb/ft ²)	37	37	47	55	62	67	50			
27. Two wythes of plastered 4 1/2-in brick, 2-in airspace with glass-fiber insulation in cavity	43	50	52	61	73	78	59			
28. 2 by 4 wood studs 16 in oc with 1-in stucco on metal lath on outside and 1/2-in gypsum board on inside (8 lb/ft ²)	21	33	41	46	47	51	42			
29. 6-in solid concrete with 1/2-in plaster both sides (80 lb/ft ²)	39	42	50	58	64	67	53			
<i>Floor-Ceilings:³</i>										
30. 2 by 10 wood joists 16 in oc with 1/2-in plywood subfloor under 25/32-in oak on floor side, and 5/8-in gypsum board nailed to joists on ceiling side (10 lb/ft ²)	23	32	36	45	49	56	37	32		

Building Construction	Transmission Loss (dB)						STC Rating	IIC Rating†
	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz		
31 Construction no. 30 with 5/8-in gypsum board screwed to resilient channels spaced 24 in oc perpendicular to joists	30	35	44	50	54	60	47	39
32 Construction no. 31 with 3-in glass-fiber insulation in cavity	36	40	45	52	58	64	49	46
33 4-in reinforced concrete slab (54 lb/ft ²)	48	42	45	56	57	66	44	25
34 14-in precast concrete tees with 2-in concrete topping on 2-in slab (75 lb/ft ²)	39	45	50	52	60	68	54	24
35 6-in reinforced concrete slab (75 lb/ft ²)	38	43	52	59	67	72	55	34
36 6-in reinforced concrete slab with 3/4-in T&G wood flooring on 1 1/2 by 2 wooden battens floated on 1-in glass fiber (83 lb/ft ²)	38	44	52	55	60	65	55	57
37 18-in steel joists 16 in oc with 1 5/8-in concrete on 5/8-in plywood under heavy carpet laid on pad, and 5/8-in gypsum board attached to joists on ceiling side (20 lb/ft ²)	27	37	45	54	60	65	47	62
Roof:								
38 3 by 8 wood beams 32 in oc with 2 by 6 T&G planks, asphalt felt built-up roofing, and gravel topping	29	33	37	44	55	63	43	
39 Construction no. 38 with 2 by 4s 16 in oc between beams, 1/2-in gypsum board supported by metal channels on ceiling side with 4-in glass-fiber insulation in cavity	35	42	49	62	67	79	53	
40 Corrugated steel, 24 gauge with 1 3/8-in sprayed cellulose insulation on ceiling side (1.8 lb/ft ²)	17	22	26	30	35	41	30	
41 2 1/2-in sand and gravel concrete (148 lb/ft ²) on 28 gauge corrugated steel supported by 14-in-deep steel bar joists with 1/2-in gypsum plaster on metal lath attached to metal furring channels 13 1/2 in oc on ceiling side (41 lb/ft ²)	32	46	45	50	57	61	49	
Doors:								
42 Louvered door, 25 to 30% open	10	12	12	12	12	11	12	
43 1 3/4-in hollow-core wood door, no gaskets, 1/4-in air gap at sill (1.5 lb/ft ²)	14	19	23	18	17	21	19	
44 Construction no. 43 with gaskets and drop seal	19	22	25	19	20	29	21	
45 1 3/4-in solid-core wood door with gaskets and drop seal (4.5 lb/ft ²)	29	31	31	31	39	43	34	
46 1 3/4-in hollow-core 16 gauge steel door, glass-fiber filled, with gaskets and drop seal (7 lb/ft ²)	23	28	36	41	39	44	38	
Glass: [‡]								
47 1/8-in monolithic float glass (1.4 lb/ft ²)	18	21	26	31	33	22	26	
48 1/4-in monolithic float glass (2.9 lb/ft ²)	25	28	31	34	30	37	31	
49 1/2-in insulated glass: 1/8- + 1/8-in double glass with 1/4-in airspace (3.3 lb/ft ²)	21	26	24	33	44	34	28	
50 1/4- + 1/8-in double glass with 2-in airspace	18	31	35	42	44	44	39	
51 Construction no. 50 with 4-in airspace	21	32	42	48	48	44	43	
52 1/4-in laminated glass, 30-mil plastic interlayer (3.6 lb/ft ²)	25	28	32	35	36	43	35	
53 Double glass: 1/4-in laminated + 3/16-in monolithic glass with 2-in airspace (5.9 lb/ft ²)	25	34	44	47	48	55	45	
54 Double glass: 1/4-in laminated + 3/16-in monolithic glass with 4-in airspace (5.9 lb/ft ²)	36	37	48	51	50	58	48	
55 Double glass: 1/4-in laminated + 1/4-in laminated with 1/2-in airspace (7.2 lb/ft ²)	21	30	40	44	46	57	42	


† IIC (impact isolation class) is a single-number rating of the impact sound transmission performance of a floor-ceiling construction tested over a standard frequency range. The higher the IIC, the more efficient the construction will be for reducing impact sound transmission. INR (impact noise rating) previously was used as the single-number rating of impact noise isolation. To convert the older INR data to IIC, add 51 to the INR number.

‡ A wide range of TL and STC performance can be achieved by gypsum wallboard constructions. Refer to ASTM E 90 laboratory report and literature from manufacturers for specific details such as type of gypsum board; gauge, width, and spacing of steel studs; glass-fiber or mineral-fiber insulation thickness and density; and complete installation recommendations.




Appendix G: Building Plans


Terrace/Ground Floor Plan



First Floor Plan



Typical Upper Floor Plan




North and West Elevations




East and South Elevations




Foundation Plan



Typical Structural Plan



Roof Mechanical Plan





Appendix H: Bibliography

1. ACI 318-08 *Building Code Requirements for Structural Concrete* published in January 2008 by the American Concrete Institute.
2. AISC *Design Guide 19: Fire Resistance of Structural Steel Framing* published in December 2005 by the American Institute of Steel Construction, Inc.
3. AISC *Seismic Design Manual Second Printing* published in October 2006 by the American Institute of Steel Construction, Inc.
4. AISC 13th Edition *Steel Construction Manual* published in December 2005 by the American Institute of Steel Construction, Inc.
5. ASCE/SEI 7-05 *Minimum Design Loads for Buildings and Other Structures* published in 2006 by the American Society of Civil Engineers.
6. Das, Braja M. *Principles of Foundation Engineering*. 6th ed. Boston: Course Technology, 2006.
7. <http://www.glwi.uwm.edu/research/genomics/ecoli/greenroof/roofinstall.php>
8. <http://www.greenroofs.org>
9. IBC 2006 *International Building Code* published in January 2006 by the International Code Council, Inc.
10. IBC 2006 *Structural/Seismic Design Manual: Building Design Examples for Steel and Concrete*. Published in 2006 by SEAOC
11. IBC 2006 *Structural/Seismic Design Manual: Code Application Examples*. Published in 2006 by SEAOC
12. Lupez, Walterio and Sabelli, Rafael *Seismic Design of Buckling-Restrained Braced Frames* published 2004 by Structural Steel Educational Council
13. Ramsey, Charles George, and Harold Reeve Sleeper. *Architectural Graphic Standards*. Ed. Bruce Bassler. 11th ed. New York: Wiley, 2008.
14. *Vulcraft Steel Roof and Floor Deck* published 2007 by The Nucor Corporation
15. Waier, Philip R R.S. *Means Building Construction Cost Data 2009. 67th ed.* published 2008 by R.S.Means, 2007.