



Jessel Elliott
Structural Option
Architectural Engineering
Senior Thesis 2012
Advisor: Dr. Richard Behr

Bed Tower Addition @
Appleton Medical Center





Outline

Introduction

Existing Structural System

Proposal

Structural Depth

Architectural Breadth

Conclusion



Design Team and Location

Introduction

Existing Structural System

Proposal

Structural Depth

Architectural Breadth

Conclusion

Architect

Structural

Construction

Civil


Mechanical

Electrical

Fire Protection

Johnson

Johnson



General Information

Introduction

Existing Structural System

Proposal

Structural Depth

Architectural Breadth

Conclusion

# of Stories:	8 plus a penthouse
Total Height:	127'-3" total height
Total Area:	152,330 sq. ft.
Project Delivery:	June 2008 – January 2011
Total Cost:	\$59,100,000



Gravity System and Foundation

Introduction

Existing Structural System

Proposal

Structural Depth

Architectural Breadth


Conclusion

Steel Rigid Frame

Composite Beam and Deck Design

Mat Foundation

Exterior bays typically 30' long



Lateral System

Introduction

Existing Structural System

Proposal



Structural Depth

Architectural Breadth

Conclusion

**Concentrically
Braced Frames**

8 Total Frames
4 in the X-direction
1 in the Y-direction
3 at 60°



Proposal

Introduction
Existing Structural System
Proposal
Structural Depth
Architectural Breadth
Conclusion

- Move the addition to an area in San Francisco, CA
- Goals
- Modify the existing structure for change in location
- Prove there is a significant change in base shear
- Control drifts
- Use base isolation to reduce loads
- Model the building to displace between the min. and max design displacements
- Compare displacements and drifts of a modified structure and the existing structure

Architecture Breadth

- Find a way to cover up the moat
- Do case studies on surrounding buildings
- Use Sketch-up to show changes in façade

Construction Breadth

- Do a cost and schedule analysis
- Check feasibility of base isolation

New Parameters

Introduction
Existing Structural System
Proposal

Structural Depth

Modified Braced Frames

Base Isolation

Architectural Breadth

Conclusion



S_{ds} :

0.045g

S_{d1} :

0.045g

SDC :

A

S_{ds} :

1.000g

S_{d1} :


0.553g

SDC :


D

Change in Column/Bracing Size


- Introduction
- Existing Structural System
- Proposal
 - Structural Depth**
 - Modified Braced Frames*
 - Base Isolation*
 - Architectural Breadth
 - Conclusion




Frame 13




Frame 12




Frame 5




Frame 2




Frame J



Frame XA



Frame XC



History of Base Isolation

Introduction

Existing Structural System

Proposal

Structural Depth

Modified Braced Frames

Base Isolation


Architectural Breadth

Conclusion

From: National Earthquake Hazards
Reduction Program (NEHRP)



- 200 buildings
- Use of damping elements to reduce lateral forces
- Control inter-story drifts
- 3 components to base isolated building

From University of Buffalo



Base Isolation Elements

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
 - Modified Braced Frames*
 - Base Isolation*
- Architectural Breadth
- Conclusion



Base Isolation Elements

Introduction
Existing Structural System
Proposal





Structural Depth

Modified Braced Frames

Base Isolation

Architectural Breadth

Conclusion



Design of Base Isolation

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
 - Modified Braced Frames
 - Base Isolation**
- Architectural Breadth
- Conclusion

$$K_{Dmax} = \frac{2.19 \sqrt{k} S_{D1} W K_{Dmin}}{4\pi^2 D_D \sqrt{B_D \min g k}}$$

$$K_{Mmax} = \frac{(1.9 \sqrt{k} S_{M1} T_M)}{2.4\pi^2 T_M \sqrt{K_{Mmin} B_M \min g}}$$

$$V_b = K_{Dmax} D_D$$

$$V_s = \frac{K_{Dmax} D_D}{R_I}$$

Where,
 S_{D1} and S_{M1} = spectral coefficients
 B_D and B_M = damping coefficients
 T_D and T_M = isolated periods
 g = gravitation acceleration (in/s²)
 W = weight of the building
 K_{Dmin} and K_{Mmin} = minimum eff. horizontal stiffness
 k = $\pm\%$ variation

V_b = minimum lateral seismic force on elements below the superstructure
 V_s = minimum shear force on superstructure as if it were fixed

Assuming

$$T_{fixed} = 1.09 \text{ s}$$

Then,

$$T_D = 4.64 \text{ s}$$

$$T_M = 5.46 \text{ s}$$

$$D_D = 18.61 \text{ in}$$

$$D_M = 32.86 \text{ in}$$

$$K_{Dmin} = 81 \text{ k/in}$$

$$V_b = 1845 \text{ kips}$$

$$V_s = 1640 \text{ kips}$$

Design of Base Isolation

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
- Modified Braced Frames*
- Base Isolation*
- Architectural Breadth
- Conclusion


Seismic Load Calculations						
Level	w	Level	Ht. (ft)	Weight (k)	F _x	M (k-ft)
		1	0	0	0	0
10		2	12.25	2124.20	21.24	260.21
9		3	25.64583	2529.80	25.30	648.79
8		4	37.25	2207.10	22.07	822.14
7		5	51.25	2506.20	25.06	1284.43
6		6	65.25	2408.60	24.09	1571.61
5		7	79.25	2389.20	23.89	1893.44
4		8	93.25	2390.30	23.90	2228.95
3		9	107.25	2334.60	23.35	2503.86
2		10	127.75	550.10	5.50	702.75
						65
Base Shear						5112.765
Base Shear						194.40
Overturning M						11916.2

-67.92%

Vertical Distribution of Forces (V = 1640 kips)							
Level	w _x (kips)	h _x (ft)	Not used for Vertical Distribution of Isolated Structures	w _x h _x	C _{vx}	F _x (kips)	M (k-ft)
10	512	127.75		65408	0.054	88.7	11330.4
9	2440	107.25		261690	0.216	354.8	38057.4
8	2427	93.25		226318	0.187	306.9	28616.9
7	2426	79.25		192261	0.159	260.7	20660.7
6	2445	65.25		159536	0.132	216.3	14115.5
5	2546	51.25		130483	0.108	176.9	9067.8
4	2220	37.25		82695	0.068	112.1	4177.0
3	2530	25.64583		64884	0.054	88.0	2256.4
2	2137	12.25		26178	0.022	35.5	434.8
				1209452		1640	128716.9
Base Shear				1640	Overturning Moment		128716.9

Time History Analysis

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
 - Modified Braced Frames*
 - Base Isolation*
- Architectural Breadth
- Conclusion




Video removed to reduce to smaller file

Displacements and Drifts

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
 - Modified Braced Frames*
 - Base Isolation*
- Architectural Breadth
- Conclusion


Comparison of Structures - Loma Prieta Y-direction (all values in inches)						
Level	Frame J					
	Max Displacement		% Change	Max Drift		% Change
	Existing Structure	Modified Structure		Existing Structure	Modified Structure	
1	18.148	18.137	0.06%	0.00	0.00	
2	18.702	18.669	0.18%	1.20	1.15	4.05%
3	19.240	19.181	0.30%	1.16	1.11	4.63%
4	19.740	19.667	0.37%	1.08	1.05	2.92%
5	20.394	20.310	0.42%	1.42	1.39	1.78%
6	20.987	20.893	0.45%	1.28	1.26	1.58%
7	21.542	21.457	0.39%	1.20	1.22	-1.64%
8	22.218	22.185	0.15%	1.47	1.58	-7.60%
9	22.718	22.718	0.00%	1.08	1.16	-6.69%



Displacements and Drifts

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
 - Modified Braced Frames*
 - Base Isolation*
- Architectural Breadth
- Conclusion

Comparison of Structures - Loma Prieta X-direction (all values in inches)						
Level	Frame 13					
	Max Displacement		% Change	Max Drift		% Change
	Existing Structure	Modified Structure		Existing Structure	Modified Structure	
1	19.2	19.2	-0.09%	0.00	0.00	
2	19.8	19.8	0.13%	1.31	1.22	6.92%
3	20.3	20.3	0.28%	1.16	1.09	6.00%
4	20.8	20.7	0.35%	1.02	0.99	3.18%
5	21.5	21.4	0.35%	1.44	1.44	0.59%
6	22.1	22.0	0.34%	1.38	1.39	-0.20%
7	22.7	22.7	0.32%	1.31	1.32	-0.31%
8	23.4	23.3	0.04%	1.38	1.49	-8.31%
9	23.8	23.8	-0.06%	0.98	1.06	-7.49%



Displacements and Drifts

- Introduction
- Existing Structural System
- Proposal
- Structural Depth**
 - Modified Braced Frames*
 - Base Isolation*
- Architectural Breadth
- Conclusion

BASE ISOLATION WITH EXISTING STRUCTURE

Frame J Displacements and Drifts

Level	Max Displace. (in)	Max Drift (in)	Allow. Drift (in)
1	18.15	0.00	0.00
2	18.70	1.20	1.47
3	19.24	1.16	1.61
4	19.74	1.08	1.39
5	20.39	1.42	1.68
6	20.99	1.28	1.68
7	21.54	1.20	1.68
8	22.22	1.47	1.68
9	22.72	1.08	1.68
$\delta = S_9 - S_1$	4.57	$\Delta_{max} = 0.010hs_x$	

BASE ISOLATION WITH MODIFIED STRUCTURE

Frame J Displacements and Drifts


Level	Max Displace. (in)	Max Drift (in)	Allow. Drift (in)
1	18.14	0.00	0.00
2	18.67	1.15	1.47
3	19.18	1.11	1.61
4	19.67	1.05	1.39
5	20.31	1.39	1.68
6	20.89	1.26	1.68
7	21.46	1.22	1.68
8	22.18	1.58	1.68
9	22.72	1.16	1.68
$\delta = S_9 - S_1$	4.58	$\Delta_{max} = 0.010hs_x$	

Allowable Drifts

Level	Height (ft)	Allow. Drift (in)
1	0	0
2	12.25	1.47
3	25.65	1.61
4	37.25	1.39
5	51.25	1.68
6	65.25	1.68
7	79.25	1.68
8	93.25	1.68
9	107.25	1.68
10	127.25	2.40

Moat Cover-up

- Introduction
- Existing Structural System
- Proposal
- Structural Depth
- Architectural Breadth**
- Conclusion




Case Studies

- Introduction
- Existing Structural System
- Proposal
- Structural Depth
- Architectural Breadth**
- Conclusion



Student Services



Hensill Hall



Administration Building



Humanities



Humanities

Changes in Façade

- Introduction
- Existing Structural System
- Proposal
- Structural Depth
- Architectural Breadth**
- Conclusion



Summary Conclusion

Introduction
Existing Structural System
Proposal
Structural Depth
Architectural Breadth

Conclusion

- Prove there is a significant change in base shear?
- Control drifts
- Model the building to displace between the min. and max design displacements



Acknowledgements

Introduction
Existing Structural System
Proposal
Structural Depth
Architectural Breadth
Conclusion

Special Thanks to:

AE Department and Faculty

Dr. Richard Behr

Friends

Family

HGA

ThedaCare

Sheetz, Inc.



Introduction

Existing Structural System

Proposal

Structural Depth

Architectural Breadth

Conclusion

THANK YOU