

LETTER OF TRANSMITTAL

DATE: September 27, 2013

TO: Dr. Linda Hanagan
Lhanagan.engr.psu.edu

FROM: Alyssa Stangl
ams6158@psu.edu

ENCLOSED: AE 481W – Senior Thesis | Structural Technical Report 2

Dear Dr. Hanagan,

This report was prepared to be submitted for Technical Report 2 for AE 481W – Senior Thesis. It includes a thorough calculation and analysis of all dead and live gravity loads, wind loads, and seismic loads. The report was created using a combination of hand written calculations and excel spreadsheets. The calculations were summarized for the lateral loads in loading diagrams at the end of each section.

Thank you for your time reviewing this report. I look forward to discussing it with you in the near future.

Sincerely,

Alyssa Michelle Stangl

Technical Report 2

September 27, 2013

La Jolla Commons Phase II Office Tower

San Diego, California

Alyssa Stangl | Structural Option | Advisor: Dr. Linda Hanagan



Table of Contents

Executive Summary.....	3
Site Plan and Location.....	4
Abstract.....	5
Documents Used to Create this Report	6
Gravity Load Calculations.....	7
Typical Roof Bay.....	8
Typical Floor Bay	10
Non-Typical Floor Loads.....	12
Typical Exterior Wall	15
Wind Load Calculations.....	17
Hand Calculations	18
Excel Spreadsheet.....	28
Wind Load Summary.....	31
Seismic Load Calculations	33
Hand Calculations	34
Excel Spreadsheet.....	37
Seismic Load Summary	39

Executive Summary

La Jolla Commons Phase II Office Tower is a 13 story office building in San Diego, California. Each floor is about 40,320 square feet, and the structure reaches 198 feet from ground level to the top of the penthouse. With two levels of underground parking, the building extends about 20 feet below grade. Acting as an office building for LPL Financial, the building has open floor plans and large areas of glass curtain wall. La Jolla Commons Tower II received a LEED-CS Gold Certification and is the nation's largest and most advanced net-zero office building.

The building's gravity system begins with a mat foundation, two stories below grade. The mat foundation was chosen for its constructability, when compared to a system of footers and grade beams. The super structure consists of two way, flat plate, concrete slabs on a rectangular column grid. A typical bay is 30 feet by 40 feet. Each level varies in thickness – 18, 14, or 12 inches, reinforcing was used as required by code. Camber was used for the slab at each level (except Lower Level 2 where the mat foundation serves as the floor). This was done because large construction loads crack the slab, causing considerable deflections after construction and finishes are completed. Camber ranges from $\frac{1}{4}$ inch at the exterior edge of a bay to $2\frac{1}{4}$ inches at the center of the bay, creating an essentially flat slab after building loads have been applied.


Laid out at the core of the building, the lateral system of La Jolla Commons Tower II consists of reinforced concrete shear walls. Due to the high shear forces associated with earthquake loading in this Seismic Category D structure, the diaphragm is not relied upon to transfer lateral loads to the shear wall system; therefore, collector beams are used to aid in load transfer.

La Jolla Commons Tower II has two unique structural and architectural features. The north and south sides of the building feature 15 foot cantilevers that start at Level 3 and continue up to the roof level. The structure is similar to that of the rest of slab; however, it does have additional reinforcement and a thickened slab edge, creating a back-span for the cantilever. Also, the building has a plaza area on the Ground Level which essentially carves out a portion of the Ground Level and Level 2. Main building columns are exposed here, and additional 18 inch columns are added to support the slab edge above.

La Jolla Commons Tower II was designed using the 2010 California Building Code which corresponds to ASCE 7-05 and ACI 318-08. CBC 2010 and ASCE 7-05 were used to calculate live, wind, and earthquake loads. ACI 318 – 08, Chapter 21, references the design of concrete Earthquake-Resistant structures, and ASCE 7-05, Chapter 12, details the Seismic Design Requirements for Building Structures. Both of these documents were used heavily in the design of LJC II in order to account for seismic loading and detailing.

La Jolla Commons Phase II Office Tower is full of educational value. It has several structural challenges and unique conditions– punching shear, seismic loading and detailing, concrete shear wall design, and computer modeling.

Building Site Information



San Diego California (Google Maps)



Building Site Plan (Courtesy of Hines)

La Jolla Commons Phase II Office Tower

San Diego, California | LPL Financial Office Tower

Primary Project Team

Owner | Hines
 Tenant | LPL Financial
 Architect | AECOM
 Structural Engineer | Nabih Youssef Associates
 MEP Engineer | WSP Flack + Kurtz
 Civil Engineer | Leppert Engineering



General Building Data

Construction Dates | April 2012 – May 2014
 Building Cost | \$78,000,000
 Delivery Method | Design-Bid-Build
 Height | 198' - 8" | 13 Stories
 Size | 462,301 SF

Architecture

Featuring a glass curtain wall system, the building is very modern in style. The floor-to-floor height is 12 feet, and each level is very open, creating a spacious and inviting office space for the tenant, LPL Financial.

Sustainability Features

This building is the first Class A NetZero Office Building in the United States – the building returns more energy to the grid than it uses on an annual basis. La Jolla Commons Tower II also received a LEED – CS Gold Certification upon completion.



Alyssa Stangl [Structural Option]

Structural

The building structure is comprised of a two-way, flat-plate, reinforced concrete slab. This slab is supported by concrete columns on a rectangular column grid. The lateral system is made up of reinforced concrete shear walls. The structural system is also supported by a mat foundation system.



Mechanical

The mechanical system consists of chilled water floor-by-floor VAV dual path air handling units – two per floor. Each AHU will provide ventilation and cooling through underfloor air distribution. Each AHU will supply overhead air distribution to perimeter zones.

Lighting and Electrical

The lighting system utilizes high efficiency, low glare fixtures, with high power factor electronic ballasts in all fluorescent fixtures. The lighting control system will be integrated with the Building Management System, with local override switches at each floor.

Two 400 Amp, 480/277V, 3-phase, 4 wire switchboards are required to service the building. One services the lower level tenant bus riser, and the second services the upper level tenant bus riser. The building has one radiator cooled, diesel fuel standby engine generator.


Documents Used to Create This Report

- *California Building Code 2010*
 - Adopts IBC 2009 with some modifications
- *American Society of Civil Engineers*
 - ASCE 7-05 – Minimum Design Loads for Buildings
- *La Jolla Commons Phase II Office Tower*
 - Construction Documents
 - Technical Specifications

GRAVITY LOAD CALCULATIONS

Typical Roof Bay Loading

Cross Section of Roof Construction (A470-B2)



ROOF DEAD LOAD:

Adhered PVC Membrane = 2 PSF

'1/2" Dens Deck Cover Board = 2 PSF

4" Rigid Insulation = 6 PSF

Concrete Slab, 11"

$$= (150 \text{ PSF}) (11"/12") = 187.5 \text{ PSF}$$

Superimposed / Misc

Ceilings = 5 PSF

MEP = 15 PSF

Sprinklers = 3 psf

} = 23 PSF

+

$$\boxed{\text{ROOF DEAD LOAD} = 171 \text{ PSF}}$$

ROOF LIVE LOAD:

ASCE 7-05 : Ch.4 Table 4-1

$$L_r = 20 \text{ PSF}$$

Construction Documents - 5001

$$L_r = 20 \text{ PSF}$$

* Roof live load used for design is equal to the code minimum value

SNOW LOAD :

ASCE 7-05 : Ch.7

Below 1500 ft elevation $\rightarrow 0 \text{ PSF}$
 Elevation from 2000-1500 ft $\rightarrow 5 \text{ PSF}$

Site elevation is about 330ft (C103)

$$P_g = 0 \text{ PSF}$$

$$P_f = 0.7 C_e C_t I P_g$$

$$P_f = 0 \text{ PSF}$$


From Figure 7-9 ASCE 7-05 :

$$h_d = 0 \text{ ft for } P_g = 0 \text{ PSF}$$

Drift calculation will yield no drift load because $P_g = 0 \text{ PSF}$

Typical Floor Bay Loading

Cross Section of floor construction



FLOOR DEAD LOAD:

14" Concrete Slab

$$= (150 \text{ PSF}) (14"/12") = 175 \text{ PSF}$$

$$\text{Carpet + Adhesive + Pad} = 1.5 \text{ PSF}$$

Superimposed / Misc

Ceilings = 5 PSF

MEP = 15 PSF

FULLY SPRINKLED = 3 PSF

Raised access floor
(by tenant) = 15 PSF (allowance)

+

214.5

Typical floor
bay dead load = 215 PSF

Typical Floor Bay Live load:

ASCE 7-05 Chapter 4

Office live load = 50 PSF

$$\text{Interior partitions} = \frac{20 \text{ PSF}}{70 \text{ PSF}}$$

Offices, Corridors
above 1st floor = 80 PSF

→ Apply 80 psf to entire office area to allow for future layout flexibility.

Typical Bay Floor Live load = 80 PSF

→ This matches the design value from sheet S001 for office spaces = 80 PSF

Non-Typical Dead Loads:

Floors and Roofs:

- Ground to Level 13, 18" slab edges

$$= (150 \text{ PSF}) (18"/12") = \underline{\underline{225 \text{ PSF}}}$$

- Ground to Level 13, 10" core slab

$$= (150 \text{ PSF}) (10"/12") = \underline{\underline{125 \text{ PSF}}}$$

- Roof / Penthouse floor, 11" slab

$$= (150 \text{ PSF}) (11"/12") = \underline{\underline{137.5 \text{ PSF}}}$$


- Roof of Penthouse, 8" slab

$$= (150 \text{ PSF}) (8"/12") = \underline{\underline{100 \text{ PSF}}}$$

- $\frac{1}{4}'' \times 2''$ - Roof metal bar grating = 15 PSF


* From Grating Pacific Catalogue
dercussion was done.

- Built-up slab at several locations at building core on each level



See next page for
calculation

Built up slab continued :



- Lets consider on 8ft x 8ft segment

LGTWT CONCRETE

$$= (4\frac{1}{2})(115 \text{ PCF}) = 38.3 \text{ PSF}$$

Structural Slab

$$= (10\frac{1}{2})(150 \text{ PCF}) = 125 \text{ PSF}$$

Pedistals

$$(12\frac{1}{2})(6\frac{1}{2})(32')(115 \text{ PCF}) = 1840 \text{ lb}$$

$$1840 \text{ lb} / 64 \text{ ft}^2 = 28.7 \text{ PSF}$$

$$\text{TOTAL of built up slab} = \underline{\underline{192 \text{ PSF}}}$$

Special Note For
Non-Typ. DEAD LOADS :


The values provided are modifications to structural components only. The finishes, load and superimposed loads (calculated for a typical bay) needs to be added to these values for a total dead load value.

Non-Typical Live Loads:

Use	Location in Building	Design Value	ASCE 7-16 Value	Explanation (if necessary)
Lobby + Corridor	Ground level at core	100 PSF	100 PSF (first floor corridor)	
Lobby + Corridor	Above ground level around core	100 PSF	80 PSF	20 PSF was added for partitions in design to allow flexibility in layout for tenant
Core/Egress	Above ground level at core	250 PSF	N/A	Value based on egress requirements for possible future multi-tenant conditions
Exit Stairs	At building core	100 PSF	100 PSF	
Cafeteria	In lease space *	100 PSF	100 PSF (dining and restaurants)	
Fitness Center	In lease space *	100 PSF	100 PSF (gymnasiums)	
Conference Center	In lease space *	100 PSF	100 PSF	ASCE 7-16 has an office for heavier anticipated occupancy
Data Center	In lease space *	250 PSF	100 PSF (computer rooms)	PSF load determined from known equipment weights
Mech. Areas	Mechanical Rooms at Core on each level	200 PSF	N/A	Value based on industry standard and actual equipment loads if known.

Typical Exterior Wall Load:

Typical Curtain Wall Section



Wall Load Path - Gravity

The curtain wall is essentially hung by the top mullion of each unit from the slab edge. The unit then ties into the unit at the level below. The wall load goes into the slab which transfers the load into the edge columns. The columns will transfer this load down to the mat foundation, which will spread out the load to meet the bearing capacity of the soil.

Typical Curtain Wall Dead Load:

Line load at slab edge

Fiber blanket insulation

$$1.0 \text{ PCF}, 1" \rightarrow 1 \text{ PCF} (1\frac{1}{12}')(4\frac{1}{2}\frac{1}{12}) = 0.35 \text{ PLF}$$

Roller shade

$$\begin{matrix} 1 \text{ Allowance for tenant} \\ \text{selection} \end{matrix} = 5 \text{ PLF}$$

Curtain Wall Units

$$10 \text{ PSF} (4\frac{1}{2}\frac{1}{12}'' + 7') = 112 \text{ PLF}$$

$$+ \underline{\hspace{10em}}$$

$$117.35 \text{ PLF}$$

Curtain Wall Assembly Dead Load	= 118 PLF
------------------------------------	-----------

WIND LOAD CALCULATION

WIND LOAD CALCULATIONS

- ASCE 7-05 Section 6.5 - Method 2 - Analytical Procedure

1. Occupancy Category (Table 1-1)

→ II , All buildings except those in I, III, IV

2. Wind Load Importance Factor (Table 6-1, § 6.5.5)

$I = 1.00$, for Category II
Non-Hurricane prone

3. Basic Wind Speed (Figure 6-1)

$$V = 85 \text{ mph}$$

4. Wind Load Parameters

a. Wind Directionality Factor, K_d (Table 6-4)

$$K_d = 0.85$$

b. Exposure Category (§ 10.5.6.3)

Exposure C

c. Topographic Factor, K_{zt} (Figure 6-4-1)

No hill, $K_{zt} = 1.0$

d. GUST EFFECT FACTOR (§ C 6.5.8)i. Building Natural Frequency (§ C 6.5.9)

- 26.9.2.1 Limitations for approx. natural frequency:

$$\begin{aligned} \textcircled{1} \quad h &= 198' - 8'' < 300' & \checkmark \\ \textcircled{2} \quad 4(115') &= 460' > 198' - 8'' & \checkmark \end{aligned}$$

Limits are met.

- Approx. natural period for concrete shearwall systems:

$$T_n = 385(C_w)^{0.5} / H$$

$$C_w = \frac{100}{A_B} \sum_{i=1}^n \left(\frac{H}{h_i} \right)^2 \frac{A_i}{\left[1 + 0.83 \left(\frac{h_i}{D_i} \right)^2 \right]}$$

$$H = 198.67 \text{ ft}$$

$$\begin{aligned} A_B &= (315')(123.67') \\ &= 39,000 \text{ SF} \end{aligned}$$

$$\text{SW U, G: } h_i = 198.67 \text{ ft}$$

$$D_i = 30 \text{ ft}$$

$$A_i = (30')(14''/12'') = 35 \text{ ft}^2$$

$$\left(\frac{198.67}{198.67} \right)^2 \frac{35}{1 + 0.83 \left(\frac{198.67}{30} \right)^2} = 5.40$$

$$\text{SW S, R, K, J: } h_i = 174.34 \text{ ft}$$

$$D_i = 30 \text{ ft}$$

$$A_i = (30')(18''/12'') = 45 \text{ ft}^2$$

$$\left(\frac{198.67}{174.34} \right)^2 \frac{45}{\left[1 + 0.83 \left(\frac{174.34}{30} \right)^2 \right]} = 2.01$$

$$\text{SW O, N: } h_i = 198.67 \text{ ft}$$

$$D_i = 20 \text{ ft}$$

$$A_i = (20')(12''/12'') = 20 \text{ ft}^2$$

$$\left(\frac{198.67}{198.67} \right)^2 \frac{20}{\left[1 + 0.83 \left(\frac{198.67}{20} \right)^2 \right]} = 0.241$$

$$\begin{array}{l} \text{SW 5. NORTH} : h_i = 198.67 \text{ ft} \\ \text{+ 4 SOUTH} : D_i = 17 \text{ ft} \\ A_i = (17 \text{ ft})(18''/12'') = 25.5 \text{ ft}^2 \end{array}$$

$$\left(\frac{198.67}{198.67}\right)^2 \frac{25.5}{\left[1 + 0.83 \left(\frac{198.67}{17}\right)^2\right]} = 0.223$$

$$\begin{array}{l} \text{SW 5 SOUTH} : h_i = 198.67 \text{ ft} \\ \text{+ 4 NORTH} : D_i = 17 \text{ ft} \\ A_i = (17 \text{ ft})(26''/12'') = 36.83 \text{ ft}^2 \end{array}$$

$$\left(\frac{198.67}{198.67}\right)^2 \frac{36.83}{\left[1 + 0.83 \left(\frac{198.67}{17}\right)^2\right]} = 0.322$$

$$\begin{array}{l} \text{SW 4 and 4.7} : h_i = 174.34 \text{ ft} \\ D_i = 30 \text{ ft} \\ A_i = (30')(14''/12'') = 35 \text{ ft}^2 \end{array}$$

$$\left(\frac{198.67}{174.34}\right)^2 \frac{35}{\left[1 + 0.83 \left(\frac{174.34}{30}\right)^2\right]} = 1.57$$

NORTH-SOUTH:

$$\sum \left(\frac{A_i}{h_i}\right)^2 \frac{A_i}{\left[1 + 0.83 \left(\frac{h_i}{D_i}\right)^2\right]} = 2(0.223) + 2(0.322) + 2(1.57) = 4.23$$

$$C_w = \frac{100}{39000 \text{ SF}} (4.23) = 0.01085$$

$$n_{N-S} = 385(0.01085)^{0.5} / 198.67$$

$$n_{N-S} = 0.202 \text{ Hz}$$

EAST-WEST:

$$\sum \left(\frac{A_i}{h_i}\right)^2 \frac{A_i}{\left[1 + 0.83 \left(\frac{h_i}{D_i}\right)^2\right]}$$

$$= 2(5.6) + 4(2.01) + 2(0.241) = 19.72$$

$$C_w = \frac{100}{39000 \text{ SF}} (19.72) = 0.05057$$

$$n_{E-W} = 385(0.05057)^{0.5} / 198.67$$

$$n_{E-W} = 0.436 \text{ Hz}$$

\therefore Flexible ($n_a < 1 \text{ Hz}$) in both directions

ii. Flexible Structures (§ 6.5.8.2)

$$G_f = 0.925 \left[\frac{1 + 1.7 I_{\bar{z}} \sqrt{g_a^2 Q^2 + g_v^2 R^2}}{1 + 1.7 g_v I_{\bar{z}}} \right]$$

NORTH - SOUTH : $g_a = g_v = 3.4$

$$\bar{z} = \max \begin{cases} 0.6h = 0.6(198.67 \text{ ft}) = 119.2 \text{ ft} \\ z_{\min} = 15 \text{ ft} \end{cases}$$

$$\bar{z} = 119.2 \text{ ft}$$

$$I_{\bar{z}} = C \left(\frac{33}{\bar{z}} \right)^{1/6}, \quad C = 0.20$$

$$= 0.20 \left(\frac{33}{119.2} \right)^{1/6}$$

$$I_{\bar{z}} = 0.161$$

$$L_{\bar{z}} = l \left(\frac{\bar{z}}{33} \right)^{\bar{\alpha}}, \quad \bar{\alpha} = 1/5, \quad l = 500 \text{ ft}$$

$$= (500) \left(\frac{119.2}{33} \right)^{1/5}$$

$$L_{\bar{z}} = 646.43$$

$$\bar{v}_{\bar{z}} = \bar{b} \left(\frac{\bar{z}}{33} \right)^{\bar{\alpha}} V \left(\frac{88}{60} \right), \quad \bar{b} = 0.65, \quad \bar{\alpha} = 1/6.5$$

$$= 0.65 \left(\frac{119.2}{33} \right)^{1/6.5} (90) (88/60)$$

$$\bar{v}_{\bar{z}} = 104.54 \text{ ft/s}$$

$$Q_{NS} = \sqrt{\frac{1}{1 + 0.63 \left(\frac{B+h}{L_{\bar{z}}} \right)^{0.63}}}, \quad B = 115 \text{ ft}, \quad h = 198.67 \text{ ft}$$

$$= \frac{1}{1 + 0.63 \left(\frac{115 + 198.67}{646.43} \right)^{0.63}}$$

$$Q_{NS} = 0.715$$

North-South Gust Factor (cont.)

$$g_R = \sqrt{2 \ln(3000 n_1)} + \frac{0.577}{\sqrt{2 \ln(3000 n_1)}}$$

$$= \sqrt{2 \ln(3000 \times 0.202)} + \frac{0.577}{\sqrt{2 \ln(3000 \times 0.202)}}$$

$$\underline{g_R = 3.79}$$

$$N_1 = \frac{n_1 L \bar{z}}{\bar{V}_{\bar{z}}} = \frac{(0.202)(646.43)}{104.54}$$

$$\underline{N_1 = 1.25}$$

$$R_n = \frac{7.47 N_1}{(1 + 10.3 N_1)^{5/3}} = \frac{7.47 (1.25)}{(1 + 10.3 (1.25))^{5/3}}$$

$$\underline{R_n = 0.117}$$

$$n(R_n) = 4.6 n_1 h / \bar{V}_{\bar{z}} = 4.6 (0.202) (198.67) / 104.54$$

$$= 1.766$$

$$n(R_B) = 4.6 n_1 B / \bar{V}_{\bar{z}} = 4.6 (0.202) (115) / 104.54$$

$$= 1.022$$

$$n(R_L) = 15.4 n_1 L / \bar{V}_{\bar{z}} = 15.4 (0.202) (279) / 104.54$$

$$= 8.30$$

$$R_n = \frac{1}{n} - \frac{1}{2n^2} (1 - e^{-2n})$$

$$= \frac{1}{1.766} - \frac{1}{2(1.766)^2} (1 - e^{-2(1.766)})$$

$$\underline{R_n = 0.411}$$

$$R_B = \frac{1}{1.022} - \frac{1}{2(1.022)^2} (1 - e^{-2(1.022)})$$

$$\underline{R_B = 0.562}$$

North-South GUST Factor Cont.

$$R_L = \frac{1}{8.30} - \frac{1}{2(8.3)^2} (1 - e^{-2(8.3)})$$

$$\underline{R_L = 0.113}$$

β = damping ratio, unknown however
from AE 538 most buildings
have a β of 5-7%.

$$\beta = 0.05$$

$$R = \sqrt{\frac{1}{\beta} R_n R_h R_B (0.53 + 0.47 R_L)}$$

$$= \sqrt{\frac{1}{0.05} (0.117)(0.411)(0.502) (0.53 + 0.47(0.113))}$$

$$R = 0.561$$

$$G_{F,NS} = 0.925 \left[\frac{1 + 1.7(0.161) \sqrt{(3.4)^2 (.715)^2 + (3.79)^2 (0.561)^2}}{1 + 1.7(3.4)(0.161)} \right]$$

$$\boxed{G_{F,NS} = 0.903}$$

EAST-WEST GUST FACTOR :

$$\bar{z} = 119.2 \text{ ft}$$

$$I_{\bar{z}} = 0.161 \text{ ft}$$

$$L_{\bar{z}} = 646.43$$

$$\bar{V}_{\bar{z}} = 104.54 \text{ ft/s}$$

$$Q_{EW} = \sqrt{\frac{1}{1 + 0.63 \left(\frac{B+h}{L_{\bar{z}}} \right)^{0.03}}}$$

$$B = 279 \text{ ft}$$

$$h = 198.67 \text{ ft}$$

$$= \sqrt{\frac{1}{1 + 0.63 \left(\frac{279 + 198.67}{646.43} \right)^{0.03}}}$$

$$Q_{EW} = 0.811$$

$$g_R = \sqrt{2 \ln(3000 \times 0.436)} + \frac{0.577}{\sqrt{2 \ln(3000 \times 0.436)}}$$

$$g_R = 3.99$$

$$N_1 = \frac{n_1 L_{\bar{z}}}{\bar{V}_{\bar{z}}} = \frac{(0.436)(646.43)}{104.54}$$

$$N_1 = 2.70$$

$$R_n = \frac{7.47 N_1}{(1 + 10.3 N_1)^{5/3}} = \frac{7.47 (2.7)}{(1 + 10.3 (2.7))^{5/3}}$$

$$R_n = 0.0745$$

$$n(R_B) = 4.6 (0.436) (279) / 104.54$$

$$= 5.35$$

$$n(R_L) = 15.4 (0.436) (115) / 104.54$$

$$= 7.39$$

$$n(R_n) = 4.6 n_1 h / \bar{V}_{\bar{z}} = 4.6 (0.436) (198.67) / 104.54$$

$$= 3.81$$

East West gust factor cont.

$$R_n = \frac{1}{3.81} - \frac{1}{2(3.81)^2} (1 - e^{-2(3.81)})$$

$$\underline{R_n = 0.228}$$

$$R_B = \frac{1}{5.35} - \frac{1}{2(5.35)^2} (1 - e^{-2(5.35)})$$

$$\underline{R_B = 0.169}$$

$$R_L = \frac{1}{7.39} - \frac{1}{2(7.39)^2} (1 - e^{-2(7.39)})$$

$$\underline{R_L = 0.126}$$

$B = 0.05$ (for same reason as NS direction)

$$R = \sqrt{\frac{1}{0.05} (0.0745)(0.228)(0.169)(0.53 + 0.47(0.126))}$$

$$\underline{R = 0.184}$$

$$G_{f,EW} = 0.925 \left[\frac{1 + 1.7(0.184) \sqrt{(3.4)^2 (0.811)^2 + (3.09)^2 (0.184)^2}}{1 + 1.7(3.4)(0.184)} \right]$$

$$\boxed{G_{f,EW} = 0.853}$$

e. Enclosure Classification (§ 6.5.9)
Enclosed (§ 6.2)

f. Internal pressure Coefficient (Fig. 6-5)

$$GC_{pi} = \pm 0.18$$

Interpolation for Roof Cp Values: (Fig. 6-6)

NORTH-SOUTH

$$h/L = 0.712$$

0 to 99.34 ft:	-0.9	0.5
	?	0.712
	$-1.3(0.8) = 1.04$	1.0

$$(99.34)(115) = 11424.1 > 1000 \rightarrow 0.8 \text{ reduction}$$

$$C_p = -1.2194$$

99.34 ft to 198.67 ft:

-0.9	0.5
?	0.712
-0.7	1.0

$$C_p = -0.8152$$

198.67 ft to 279 ft:

-0.5	0.5
?	0.712
-0.7	1.0

$$C_p = -0.5848$$

EAST-WEST

$$H/L = 1.728 > 1.0$$

0 to 99.34 ft :-

$$C_p = -1.3$$

$$A = (99.34)(279) = 27716 \text{ ft}^2 > 1000 \text{ ft}^2$$

$$C_p = -1.3(0.8) = \underline{-1.04}$$

99.34 ft to 115 ft :

$$C_p = -0.7$$

Interpolation for wall C_p Values: (Fig. 6-6)

NORTH-SOUTH

$$L/B = 2.43$$

-0.3	2
?	2.43
-0.2	4

$$C_p = -0.279$$

* No other C_p -values were interpolated

WIND LOADING CALCULATIONS

Equations Utilized:

$$K_z = 2.01 (z/z_g)^{2/\alpha}$$

$$q_z = 0.00256 K_z K_{rt} K_d V^2$$

$$p = q G_c C_p \text{ (MWFRS for Flexible Buildings)}$$

Constants Previously Calculated by hand:

$$k_{rt} = 1.00$$

$$k_d = 0.85$$

$$V = 85.0$$

$$I = 1.00$$

$$G_{f, NS} = 0.903$$

$$G_{f, EW} = 0.853$$

Calculating k_z and q_z - NS and SW						
Floor Number	Height above ground (z)	z_g	α	k_z	q_z	q_h
2	15.00	900	9.5	0.85	13.36	22.99
3	28.17	900	9.5	0.97	15.24	22.99
4	41.34	900	9.5	1.05	16.52	22.99
5	54.51	900	9.5	1.11	17.51	22.99
6	67.68	900	9.5	1.17	18.33	22.99
7	80.85	900	9.5	1.21	19.03	22.99
8	94.02	900	9.5	1.25	19.64	22.99
9	107.19	900	9.5	1.28	20.19	22.99
10	120.36	900	9.5	1.32	20.69	22.99
11	133.53	900	9.5	1.35	21.15	22.99
12	146.70	900	9.5	1.37	21.57	22.99
13	159.87	900	9.5	1.40	21.96	22.99
Penthouse Floor	173.04	900	9.5	1.42	22.33	22.99
Penthouse Roof	198.67	900	9.5	1.46	22.99	22.99

Wall Pressures | NORTH-SOUTH DIRECTION

Wind Pressures North-South Direction										
Floor Number	Height above ground (z)	q _z	q _h	Windward (PSF)	Leeward (PSF)	Trib Height	Trib Area (SF)	Force (k)	Story Shear (K)	Overspinning Moment (ft-k)
Ground	0.00	13.36	22.99	9.65	-5.78	7.50	2092.50	32.30	421.44	0.00
2	15.00	13.36	22.99	9.65	-5.78	14.09	1619.78	25.00	389.14	375.03
3	28.17	15.24	22.99	11.01	-5.78	13.17	1514.55	25.43	364.14	716.38
4	41.34	16.52	22.99	11.93	-5.78	13.17	1514.55	26.83	338.71	1109.27
5	54.51	17.51	22.99	12.65	-5.78	13.17	1514.55	27.92	311.87	1521.73
6	67.68	18.33	22.99	13.24	-5.78	13.17	1514.55	28.81	283.96	1949.83
7	80.85	19.03	22.99	13.74	-5.78	13.17	1514.55	29.57	255.15	2391.09
8	94.02	19.64	22.99	14.19	-5.78	13.17	1514.55	30.25	225.57	2843.77
9	107.19	20.19	22.99	14.59	-5.78	13.17	1514.55	30.85	195.33	3306.58
10	120.36	20.69	22.99	14.95	-5.78	13.17	1514.55	31.39	164.48	3778.51
11	133.53	21.15	22.99	15.28	-5.78	13.17	1514.55	31.89	133.08	4258.76
12	146.70	21.57	22.99	15.58	-5.78	13.17	1514.55	32.36	101.19	4746.68
13	159.87	21.96	22.99	15.87	-5.78	13.84	1591.03	34.44	68.83	5506.40
Penthouse Floor	173.04	22.33	22.99	16.13	-5.78	19.42	1196.30	26.22	34.39	4536.56
Penthouse Roof	198.67	22.99	22.99	16.61	-5.78	12.17	365.10	8.17	8.17	1624.11

Base Shear [k] = 421**Total Overturning Moment [ft-k] = 38665**Windward Wall C_p= 0.800

L= 279.00

Leeward Wall C_p= -0.279

B= 115.00

(interpolate)

L/B= 2.43

Wall Pressures | EAST-WEST DIRECTION

Wind Pressures East-West Direction										
Floor Number	Height above ground (z)	q _z	q _h	Windward (PSF)	Leeward (PSF)	Trib Height	Trib Area (SF)	Force (k)	Story Shear (K)	Overspinning Moment (ft-k)
1	0.00	13.36	22.99	9.12	-10.38	7.50	862.5	16.82	1166.73	0
2	15.00	13.36	22.99	9.12	-10.38	14.09	3929.7	76.63	1149.91	1149.43
3	28.17	15.24	22.99	10.40	-10.38	13.17	3674.4	76.35	1073.28	2150.90
4	41.34	16.52	22.99	11.27	-10.38	13.17	3674.4	79.57	996.93	3289.34
5	54.51	17.51	22.99	11.95	-10.38	13.17	3674.4	82.05	917.36	4472.62
6	67.68	18.33	22.99	12.51	-10.38	13.17	3674.4	84.10	835.31	5691.76
7	80.85	19.03	22.99	12.98	-10.38	13.17	3674.4	85.85	751.21	6941.05
8	94.02	19.64	22.99	13.40	-10.38	13.17	3674.4	87.39	665.36	8216.50
9	107.19	20.19	22.99	13.78	-10.38	13.17	3674.4	88.77	577.97	9515.16
10	120.36	20.69	22.99	14.12	-10.38	13.17	3674.4	90.02	489.20	10834.74
11	133.53	21.15	22.99	14.43	-10.38	13.17	3674.4	91.17	399.18	12173.40
12	146.70	21.57	22.99	14.72	-10.38	13.17	3674.4	92.23	308.01	13529.62
13	159.87	21.96	22.99	14.99	-10.38	13.84	3860.0	97.92	215.79	15654.63
Penthouse Floor	173.04	22.33	22.99	15.24	-10.38	19.42	3300.3	84.55	117.87	14631.08
Penthouse Roof	198.67	22.99	22.99	15.69	-10.38	12.17	1277.9	33.31	33.31	6618.37

Base Shear [k]= 1167**Total Overturning Moment [ft-k] = 114869**Windward Wall C_p= 0.800

L= 115.00

Leeward Wall C_p= -0.500

B= 279.00

Roof Wind Uplift | NORTH-SOUTH DIRECTION

Wind Pressures - Roof Uplift North South				
Location on Roof	Cp	G	q _h	Pressure [PSF]
0 to 99.34 ft	-1.2194	0.903	22.99	-25.32
99.34 to 198.67 ft	-0.8152	0.903	22.99	-16.92
198.67 to 279 ft	-0.5848	0.903	22.99	-12.14

h= 198.67
L= 279
h/L= 0.712


NOTE: Interpolation between h/L=0.5 and h/L=1.0 can be seen on Page 18 of hand calculations. Also, Area reduction calculation can be seen on Page 18.


Roof Wind Uplift | EAST-WEST DIRECTION

Wind Pressures - Roof Uplift East West				
Location on Roof	Cp	G	q _h	Pressure [PSF]
0 to 99.34 ft:	-1.040	0.853	22.99	-20.40
99.34 to 115 ft:	-0.700	0.853	22.99	-13.73

h= 198.67
L= 115
h/L= 1.728

NOTE: Area reduction application calculation can be seen on Page 19 of hand calculations.

NORTH-SOUTH WIND PRESSURE DIAGRAM

EAST-WEST WIND PRESSURE DIAGRAM

SEISMIC LOAD CALCULATION

SEISMIC LOAD CALCULATIONS

1. Building not exempt. ($\S\ 11.1.2$)
2. Design Spectral Response Acceleration ($\S\ 11.4$)
 - a) Site Class Definition = C
 - b) Acceleration Parameters

$$S_g = 1.418g$$

$$S_1 = 0.527g$$

- c) Site Class Effects ($\S\ 11.4.3$)

$$F_a = 1.0$$

$$F_v = 1.3$$

$$S_{MS} = (1.0)(1.418g) \rightarrow S_{MS} = 1.418g$$

$$S_{MI} = (1.3)(0.527g) \rightarrow S_{MI} = 0.6851g$$

- d) Determine Spectral Acceleration Parameters ($\S\ 11.4.4$)

$$\begin{aligned} S_{DS} &= \frac{2}{3} S_{MS} \\ &= \frac{2}{3} (1.418g) \rightarrow S_{DS} = 0.9453 \end{aligned}$$

$$\begin{aligned} S_{DI} &= \frac{2}{3} S_{MI} \\ &= \frac{2}{3} (0.6851g) \rightarrow S_{DI} = 0.4567 \end{aligned}$$

3. Find Seismic Design Category ($\S\ 11.5 + \S\ 11.6$)

Occupancy Category = II

$$I = 1.0$$

$$S_{DS} = 0.9453 \geq 0.5 \rightarrow S_{DC} = D$$

4. Analysis Procedure Selection (Table 12.6-1)

Equivalent Lateral Force Procedure

5. Determine Response Modification Factor

B.5 - Special reinforced concrete shear walls

$$R = 6$$

6. Find Period (T_a) (§ 12.8.2)

$$T_a = C_t h_n^x$$

$$C_t = 0.02$$

$$h_n = 198.17 \text{ ft}$$

$$x = 0.75$$

$$T_a = 0.02 (198.17)^{0.75} \rightarrow T_a = 1.056 \text{ s}$$

7. Determine, T_L (Fig. 22-15)

$$T_L = 8 \text{ s}$$

8. Find C_s (seismic response coefficient) (§ 12.8.1.1)

$$C_s = \frac{S_{DS}}{(R/I)} = \frac{0.9453}{(4/1.0)} \rightarrow C_s = 0.1574$$

$$T_a = 1.056 \text{ s} < T_L = 8 \text{ s}$$

$$C_s = \frac{S_{DL}}{T(R/I)} = \frac{0.4561}{(1.056)(4/1.0)} = 0.0720$$

$$C_s = \begin{cases} 0.1574 \\ 0.0720 \end{cases} = 0.0720 > 0.01 \quad \checkmark$$

$$\underline{C_s = 0.0720}$$

9. Weight Calculation: See excel sheet Page. 28 of this document.

10. Calculate Base Shear (Eq. 12.B-1)

$$V = C_s W$$

$$= (0.0720)(88979 \text{ k})$$

$$V = \underline{6406.5 \text{ k}}$$

11. Determine Story Forces

Find K:

	0.5s	K=1
T=1.0505		K=2
2.5s		K=2

$$\frac{2-1}{2.5-0.5} = \frac{K-1}{1.0505-0.5}$$

$$K = \underline{1.278}$$

* See excel sheet for the rest of *
the seismic force calculation.
(Pg. 29 of this document)

SIESMIC LOAD CALCULATIONS

Floor Weight Calculation					
Floor Number	Dead Load	Partition Load	Total Weight (PSF)	Floor Area (ft ²)	Weight (kip)
Penthouse Roof	133	0	133	6704	892
Penthouse Floor	171	0	171	29703	5079
13	215	20	235	29703	6980
12	215	20	235	29703	6980
11	215	20	235	29703	6980
10	215	20	235	29703	6980
9	215	20	235	29703	6980
8	215	20	235	29703	6980
7	215	20	235	29703	6980
6	215	20	235	29703	6980
5	215	20	235	29703	6980
4	215	20	235	29703	6980
3	215	20	235	29703	6980
2	215	20	235	26494	6226
					Total Weight = 88979

Seismic Story Forces

T= 1.056 s
 k= 1.278
 Vb= 6406.5 k

Siesmic Load vs. Height Diagram

