







APPENDIX A | LUMINAIRE SCHEDULE



INTERIOR LIGHTING FIXTURES – CLASSIFICATION L

TYPE	SPECIFICATION	MANUFACTURER	LAMP TYPE	QTY. OF LAMPS	LAMP WATTAGE	TOTAL WATTAGE	VOLTAGE
<p>L1</p> 	<p>RECESSED PERIMETER COVE LINEAR FLUORESCENT WALL GRAZER</p> <p>LAMPING (CROSS SECTION): (1) 3'-0"/4'-0" 28 WATT T5 LINEAR. FLUOR. BEAM SPREAD DISTRIBUTION: DOWNLIGHT GRAZE APERTURE SIZE: 6" WIDTH BALLAST: ELECTRIC PROGRAM START < 10% THD CONTROL: PROGRAM RELAY MOUNTING: ACOUSTIC PANEL CEILING</p> <p>LOCATION: ELEVATOR LOBBY</p>	FOCAL POINT: MINI-GRAZER	F28T5	1	28	8 WLF	277
CATALOG NUMBER: FMG-NS-1T5HO-1C-277-S-WH-24'							
<p>L2</p> 	<p>RECESSED ROUND TRIMLESS DOWNLIGHT 1" REGRESS</p> <p>COLOR TEMPERATURE: 3000K COLOR RENDERING INDEX: 80 OR ABOVE APERTURE SIZE: 4.5" DELIVERED LUMENS: 1500lms LED LIFE: L70 AT 50,000 HOURS BEAM SPREAD DISTRIBUTION: 50° FINISH: WHITE CONTROL: 0-10V DIMMING DRIVER MOUNTING: ACOUSTIC PANEL CEILING</p> <p>LOCATION: ELEVATOR LOBBY AND WORKSTATION</p>	USA1: BEVELED 2.0	LED	-	-	20	277
CATALOG NUMBER: LRLD4-9020-M2-30KS-50-NCSM2-277-DIML2							
<p>L3</p> 	<p>1' x 4' RECESSED VOLUMETRIC DISTRIBUTION LUMINAIRE</p> <p>COLOR TEMPERATURE: 3000K COLOR RENDERING INDEX: 80 OR ABOVE MAXIMUM WATTAGE: 22.9W DELIVERED LUMENS: 1207lms LED LIFE: L70 AT 50,000 HOURS BEAM SPREAD DISTRIBUTION: ASYMMETRIC FINISH: MATTE WHITE HOUSING CONTROL: 0-10V ANALOG DIMMING DRIVER MOUNTING: DRYWALL</p> <p>LOCATION: WORKSTATION</p>	LITHONIA: RT5	F28T5	1	28	39	277
CATALOG NUMBER: RT5-1-28T5-MVOLT-GEB115-LPM830P							
<p>L4</p> 	<p>LOW WATTAGE LINEAR LED SLOT LUMINAIRE</p> <p>COLOR TEMPERATURE: 3000K COLOR RENDERING INDEX: 80 OR ABOVE MAXIMUM WATTAGE: 22.9W DELIVERED LUMENS: 1207lms LED LIFE: L70 AT 50,000 HOURS BEAM SPREAD DISTRIBUTION: ASYMMETRIC FINISH: MATTE WHITE HOUSING CONTROL: 0-10V ANALOG DIMMING DRIVER MOUNTING: GRID</p> <p>LOCATION: MEETING ROOM</p>	FOCAL POINT: TRACE	LED	-	-	23 W per 4'	277
CATALOG NUMBER: FTRL-AC-LL1-30K-1C-277-LD1-G-FL-WH-28'							
<p>L5</p> 	<p>RECESSED LED LINEAR DOWNLIGHT FLUSH LENS</p> <p>LAMPING (CROSS SECTION): (1) 3'-0"/4'-0" 28 WATT T5 LINEAR. FLUOR. BEAM SPREAD DISTRIBUTION: DOWNLIGHT GRAZE APERTURE SIZE: 6" WIDTH BALLAST: ELECTRIC PROGRAM START < 10% THD CONTROL: PROGRAM RELAY MOUNTING: ARMSTRONG TECHZONE LAY-IN</p> <p>LOCATION: MEETING ROOM</p>	FOCAL POINT: SEEM 6	F28T5	1	28	8 WLF	277
CATALOG NUMBER: FSM6-FL-2T5-1C-277-S-G1-WH-68'							

INTERIOR LIGHTING FIXTURES – CLASSIFICATION L

TYPE	SPECIFICATION	MANUFACTURER	LAMP TYPE	QTY. OF LAMPS	LAMP WATTAGE	TOTAL WATTAGE	VOLTAGE
<p>L6</p> 	<p>RECESSED ROUND TRIMLESS WALL WASHER 1" REGRESS</p> <p>COLOR TEMPERATURE: 3000K COLOR RENDERING INDEX: 80 OR ABOVE APERTURE SIZE: 4.5" DELIVERED LUMENS: 950lms LED LIFE: L70 AT 50,000 HOURS BEAM SPREAD DISTRIBUTION: WALLWASH FINISH: WHITE CONTROL: 0-10V DIMMING DRIVER MOUNTING: ACOUSTIC PANEL CEILING</p> <p>LOCATION: MEETING ROOM</p>	USAI: BEVELED 2.0	LED	-	-	24	277
CATALOG NUMBER: LRTW4-6024-C2-30KS-NC-277-DIML2							

EXTERIOR LIGHTING FIXTURES – CLASSIFICATION S

TYPE	SPECIFICATION	MANUFACTURER	LAMP TYPE	QTY. OF LAMPS	LAMP WATTAGE	TOTAL WATTAGE	VOLTAGE
<p>S1</p> 	<p>LED AREA LUMINAIRE</p> <p>LAMPING: 63 LEDS (ONE LIGHT ENGINE) COLOR TEMPERATURE: 3000K COLOR RENDERING INDEX: 80 OR ABOVE LED LIFE: L70 AT 50,000 HOURS BEAM SPREAD DISTRIBUTION: SR2 CONTROL: PROGRAM RELAY POLE HEIGHT: 11'</p> <p>LOCATION: EXTERIOR PLAZA</p>	LITHONIA: OMERO	LED	-	-	73 W	277
CATALOG NUMBER: MRP LED-1-63B350/30K-SR2-277-DFL-DBLXD							
<p>S2</p> 	<p>LED LIGHTING INTEGRATED WITHIN HANDRAIL</p> <p>LAMPING: WARM WHITE LED COLOR TEMPERATURE: 3000K COLOR RENDERING INDEX: 80 OR ABOVE MAXIMUM WATTAGE: 3 PER FOOT DELIVERED LUMENS: 219 PER FOOT LED LIFE: L70 AT 50,000 HOURS BEAM SPREAD DISTRIBUTION: ASYMMETRIC CROSS SECTION SIZE: PER HANDRAIL DETAILS FINISH: STAINLESS STEEL POLISHED POWER SUPPLY: FULL RANGE DIMMING CONTROL: PROGRAMMABLE RELAY</p> <p>LOCATION: EXTERIOR PLAZA</p>	IO LIGHTING: LUXRAIL	LED	-	-	3 WLF	277
CATALOG NUMBER: 0-06-SSP-1-WM-NR-ASYM-3K-HR-277V							