

Conclusions and Recommendations



CONCLUSIONS AND FINAL RECCOMENDATIONS

The goal of this report was to design and evaluate an alternative superstructure design for Eight Tower Bridge, a high-rise office tower located in Conshohocken, Pennsylvania. The existing composite steel superstructure does adequately resist gravity and lateral loads, but the question still exists: could this building have been designed as a concrete structure?

The long spans that currently exist in Eight Tower Bridge were maintained by designing a one-way, post-tensioned beam and slab floor design. Using post-tensioning allowed for longer concrete spans, which kept the floor plan of the building open and without very many column intrusions. Two post-tension systems were designed. The system employs post-tensioning in the beams that support a 6" reinforced concrete. This system saw a maximum deflection of 0.57" under sustained loading. The second alternative flooring system increased the spacing between beams by adding post-tensioning to the slab. The maximum deflection under sustained loading of this system was found to be 0.55". The original steel system was found to have a deflection of 1.03" after a 1-3/4" camber was subtracted from the total deflection. Both of the concrete systems reduced the overall floor system depth by 3-1/4" and 5-1/4", respectively. However, this reduction in floor system depth did not correlate to a reduction in dead load, as the building's total weight actually increased.

Both concrete systems used the same columns and the same shear wall lateral force resisting system. The shear wall system designed is comprised of 8, 12" shear walls arranged around the building core. The building sees a maximum deflection of 4.66" under seismic loading in the x-direction. Under wind loading, the deflection was found to be 1.76", nearly half the deflection found under the same loading for the steel system.

A construction management study was conducted to see how changing the material of the building would affect the overall cost and construction schedule. The first concrete system resulted in a \$14.51/ square foot, while the second system came in at \$14.21/square foot. These totals are in 2001 dollars, and include material,

placement, formwork and shoring. The total steel system was totaled \$13.94/square foot, but did not include the \$500,000 dollars in change orders reported. The construction duration of both concrete systems was found to be comparable, and totaled 28 weeks when concrete was placed using a crane and bucket. If the engineer or concrete contractor could arrange to have the concrete placed by pump (a feat uncommon in high-rise construction, but not out of the question entirely), then the construction duration would only last 23 weeks. This would be a reduction of 5 weeks from the steel construction time of 28 weeks.

An unrelated mechanical systems study was conducted to explore the used of a ground source heat pump for use in heating and cooling of Eight Tower Bridge. The system currently runs a chilled water loop system that uses rooftop mounted cooling towers to chill the liquid in the loop. The ground source pump would use the earth's natural temperature as a reservoir for heat exchange of the liquid in the loop. However, it was found that the initial investment to implement this system heavily outweighed the payback period, which was found to be nearly 19 years for the cooling loop.

Final Recommendation:

Although the alternative concrete design results in an overall thinner floor system, which could allow for reduction in overall building height, saving money on cladding components and MEP costs, it is still suggested that Eight Tower Bridge be constructed out of steel for the following reasons:

1. The cost per square foot of the steel system is lower than the concrete systems (\$13.94/sq ft)
2. Interior finishes (i.e. drop ceiling) are more difficult to install in concrete systems, and are the desired finish for most office buildings
3. The Philadelphia region does not have very many experienced post-tensioning contractors, which could potentially cause construction issues
4. The owner, engineer and architect all have experience designing and constructing steel office buildings
5. The rooftop mechanical penthouse is most easily constructed in steel, and is strategically placed on the roof due to flood concerns, eliminating the possibility of placing equipment in the basement

ACKNOWLEDGEMENTS

I would like to extend my sincere gratitude to the people who have helped me make this senior thesis project a success. Without the help of everyone below, I would not have been able to complete this project.

Firstly, I would like to thank Skidmore, Owings & Merrill specifically Shaun Mason and Jim for their help in obtaining Eight Tower Bridge for my senior thesis project. Without their fast action in the face of disaster, I would have been in trouble.

I would also like to thank Oliver Tyrone Pulver Corporation and Brandywine Realty Trust for allowing me to conduct my research on their property.

I would like to thank the AE faculty, specifically Professor Parfitt and Dr. Hanagan, for all their work this year not just with me, but with all the students working in thesis projects. They have been a great source of guidance, more than they will know.

Next, I would like to thank all of my classmates for all their help this year. Everyone was incredibly helpful, weather it was helping to learn a computer program, getting an opinion about design options or for a good laugh late at night. All of these things contributed to my success this year.

Finally, I would like to thank all of my friends for their support this year, especially the staff of 419 Old Main. All of your endless support and cheering is what has gotten me through this challenging year. And of course, thanks to both of my parents for being my biggest supporters from day one. I could not have done life without the two of you, let alone this project. Thanks for all your encouragement and love.

REFERENCES

Aalami, Bijan O., and Jennifer D. Jurgens. Guidelines for the Design of Post-Tensioned Floors. Concrete International, March 2003.

Building Code Requirements for Structural Concrete (ACI 318-05) and Commentary (ACI318R-05). Farmington Hills, MI: American Concrete Institute, 2005.

Darwin, David, Charles Dolan, and Arthur Nilson. Design of Concrete Structures, 13th Edition. Boston, MA: McGraw Hill, 2004.

Load and Resistance Factor Design, 3rd Edition, American Institute of Steel Construction, 2001.

Naaman, Antoine E. Prestressed Concrete Analysis and Design, 2nd Edition. Ann Arbor, MI: Techno Press, 2004.

Two-Way Post-Tension Design. 12 February, 2006. Portland Cement Association.
www.cement.org/buildings.