



## List of Tables, Figures, and Charts

### 1.0 Building Overview

#### 1.1 Site, Architecture, and Construction

- Figure 1.1A Map of 440 North Broad Street, Philadelphia, PA.
- Figure 1.1B. PSDAH New Atrium Space.
- Figure 1.1C PSDAH Footprint.
- Figure 1.1D. Broad Street Entrance.

#### 1.2 Engineering Overview

- Table 1.2A Existing and New Elevators.

#### 1.3 Existing Mechanical System

- Figure 1.3A. Floor 1 Existing AHU Layout.
- Figure 1.3B Floor 2 and Floor 3 Existing AHU Layout.
- Figure 1.3C. Floor 4 and Floor 5 Existing AHU Layout.
- Figure 1.3D. AHU Air Filter.
- Table 1.3A. Ventilation Air Comparison.
- Table 1.3B. Existing System First Cost.
- Table 1.3C. Energy Consumption by Existing System.
- Table 1.3D. Existing Mechanical System Operating Cost.
- Table 1.3E. Emissions due to the Existing Mechanical System.

### 2.0 Depth Work — Alternative Mechanical Designs

#### 2.2 Overview of Systems

- Figure 2.2A. Plan of Airside VAV System.
- Figure 2.2B. DOAS/VAV Airside Riser Diagram.
- Table 2.2A. DOAS Analysis Comparison for Space FL-1 NE.

#### 2.3 Equipment

- Figure 2.3A. McQuay Packaged SWP Air Handling Unit in FL-3 S Mechanical Room.
- Figure 2.3B. SEMCO Packaged Energy Recovery System, EPC-24/EP-43
- Figure 2.3C. SEMCO Model TE3-24-3Å/TE3-43-3Å.
- Figure 2.3D. Trane's High Induction Diffuser Performance.
- Figure 2.3E. Smooth Face Linear Extrusion Panel by Sterling.
- Table 2.3B. DOAS AHU Schedule.

#### 2.4 Procedure and Calculations for Alternative Designs

- Figure 2.4A. New Service Designation for AHUs.
- Figure 2.4B. DOAS Air Handling Unit State Points.



- Figure 2.4C. Enthalpy Wheel Effectiveness – Summer.
- Figure 2.4D. Enthalpy Wheel Effectiveness – Winter.
- Table 2.4A. Space Heating & Cooling Loads with VAV as an Airside System [Btu/h].
- Table 2.4B. Space Heating & Cooling Loads w Radiant Panels as Parallel System.
- Table 2.4C. Air Properties for Design VAV Conditions.
- Table 2.4D. Peak Cooling Design Floor 4 CAV.
- Table 2.4E. Summer DOAS Outdoor, Supply, and Room Air Conditions.
- Table 2.4F. Winter DOAS Outdoor, Supply, and Room Air Conditions.
- Table 2.4G. Supply Air Reduction for Parallel VAV System.

## **2.5 Results and Recommendations**

- Chart 2.5A. Total Energy Savings Using an Electric Centrifugal Chiller—Floor 4.
- Chart 2.5B. Total Source Energy Consumption by System.
- Chart 2.5C. Mechanical System First Cost/Yearly Operating Cost.
- Table 2.5A. Yearly Operating Cost Based on Energy Consumption.
- Table 2.5B. First Cost of Base and Alternative Mechanical Systems.
- Table 2.5C. Generation Fuel Mix.
- Table 2.5D. System Emissions due to Electricity Consumption.
- Table 2.5E. Cost Summary.

## **3.0 Breadth Work — Integration of Structural System and Constructability**

### **3.2 Structural Analysis**

- Figure 3.2A. Column Section with New Floor.
- Figure 3.2B. New Mechanical Floor Above Roof.
- Figure 3.2C. Loads on Beams.
- Figure 3.2D. Top Slab without Deflection.
- Figure 3.2E. Top Slab with Deflection.
- Figure 3.2F. First Floor Columns.
- Figure 3.2G. New Floor Columns.
- Figure 3.2H. New Floor Beams.
- Figure 3.2I. Frame Plan.

### **3.3 Constructability**

- Figure 3.3A. Sequence Numbering.
- Figure 3.3B. Sequences Started and Finished.
- Figure 3.3C. VAV Critical Activity.
- Figure 3.3D. Critical Activity.
- Figure 3.3E. Site Analysis.